

**CHAPTER 4.1.9 GROUND WATER RESOURCES
DHARMAPURI DISTRICT**

INDEX

CHAPTER	PAGE NO.
INTRODUCTION	3
DHARMAPURI DISTRICT – ADMINISTRATIVE SETUP	3
1. HYDROGEOLOGY	3-7
2. GROUND WATER REGIME MONITORING	8-15
3. DYNAMIC GROUND WATER RESOURCES	15-24
4. GROUND WATER QUALITY ISSUES	24-25
5. GROUND WATER ISSUES AND CHALLENGES	25-26
6. GROUND WATER MANAGEMENT AND REGULATION	26-32
7. TOOLS AND METHODS	32-33
8. PERFORMANCE INDICATORS	33-36
9. REFORMS UNDERTAKEN/ BEING UNDERTAKEN / PROPOSED IF ANY	
10. ROAD MAPS OF ACTIVITIES/TASKS PROPOSED FOR BETTER GOVERNANCE WITH TIMELINES AND AGENCIES RESPONSIBLE FOR EACH ACTIVITY	

GROUND WATER REPORT OF DHARMAPURI DISTRICT

INTRODUCTION :

In Tamil Nadu, the surface water resources are fully utilized by various stake holders. The demand of water is increasing day by day. So, groundwater resources play a vital role for additional demand by farmers and Industries and domestic usage leads to rapid development of groundwater. About 63% of available groundwater resources are now being used. However, the development is not uniform all over the State, and in certain districts of Tamil Nadu, intensive groundwater development had led to declining water levels, increasing trend of Over Exploited and Critical Firkas, saline water intrusion, etc.

ADMINISTRATIVE SET UP

Dharmapuri District with a geographical area of 9641.03 Sq.Kms. is located on the North Western corner of the Tamil Nadu State. It lies in between North Latitude 11°47'00" and 12°53'00" and East Longitudes 77°28'00" and 78°45'00" falling in Survey of India topographical maps Nos.57L,58H, and 58E and 58I.

The Dharmapuri District comprises of 3 Revenue divisions, 10 Taluks, 18 Blocks, 22 Firkas 1106 Revenue Villages.

Dharmapuri District is totally bifurcated into 22 Firkas

1. HYDROGEOLOGY

(i) Major Geological formations:

Geology:

Geologically Dharmapuri District is covered by crystalline rocks of Archaean age.

a) Crystalline rocks:

The entire district is underlain by hard crystalline rocks of Archaean age comprising of various rock types such as Gneiss, Charnockite, etc., The Gneissic type of crystalline formation is found in the north and north eastern part of the district. Shoolagiri, Hosur, Denganikottai and Kelamangalam areas are covered by Granitic

Gneiss. Veppanapalli, Krishnagiri and parts of Kaveripaattinam areas are covered by peninsular Gneiss. Bargur, part of Kariamangalam, Palacode, Pochampalli and Uthangarai are covered by Biotite Gneiss. Part of Harur, Uthangarai and Morappur areas are covered by foliated gneiss.

Charnockite occurs in the southern part of the district, covering part of Palacode, part of Morappur, Pappireddipatti, part of Dharmapuri, Pennagaram and Nallampalli. Quartzites are found in patches in Denganikottai block. Dolerite dykes varying from few feet to few miles in length cut across the country rock in this district.

Alluvial deposits such as sand, silt, clay and gravels which are transported sediments by the river Ponnaiyar and Chinnar are found on either side of the river courses. These formations are overlying the hard rocks as a thin layer.

In Dharmapuri district, weathered thickness ranges from 8 m to 15 m bgl. And jointed formation ranges from 15 m to 60 m in general. The strike direction is generally North East – South west, dipping towards south east.

Drilling of bore holes:

The occurrence and movement of ground water in hard rock formations are restricted to open system of fractures like fissures and joints in unweathered portion and also the porous zones at weathered formations.

The State Ground and Surface Water Resources Data Center, during the course of investigation, has drilled many bore holes of depth ranging from 30 m to 300 m spread over the entire district to find out the nature and behaviour of the sub surface material. During the course of investigation, it is found that the bore wells drilled in the lineament zones, fault zones and at the intersection of faults have yielded more, ranging from 50 gpm to 250 gpm. In some of the bore wells drilled in Alapatti and Theertham villages, over flow above ground level is noticed.

There is considerable diversity in the nature of formation even the short distance. The bore hole drilled at Thumbalahalli Village Palacode Taluk yields 100 gpm. The bore hole drilled by TWAD board in the village Annasagaram has fallen in the lineament zone and the yield is more than 100 gpm. The yield of the borehole

drilled at Perumbalai village of Pennagaramtaluk is 50 gpm and borehole drilled at Maharajakadai village of Krishnagiritluk yields 200 gpm.

Aquifer parameters:

Hard rock:

The thickness of aquifer in this district varies from 10 m to 50 m below ground level. The intergranular – porosity is essentially dependent upon the intensity and degree of weathering and fracture development in the hard rock. The deep weathering has developed in gneissic formation and moderate weathering in Charnockite formation. The range of aquifer parameters in hard rock areas is given in the table below.

Parameters	Range
Well yield in LPM	Ranges between 36 and 1125 (Paiyur village – 36 lpm, Maharajakadai village – 1125 lpm)
Transmissivity (T) m ² /day	Ranges between 8 and 73 m ² /day
Permeability (K) m/day	Ranges between 0.78 and 23 m/day

(iii) Drilling:

The drilling types are different according to the formation of the terrain. In general, DTH rigs are used in Hard rock formations for drilling a borewell at a depth ranges from 30m to 200m, according to the extension of joints, fractures, lineaments, etc in an area. In Sedimentary formations, rotary rigs with different rotors used according to the Tube well’s diameter. The Bento novate clay is used in rotary rigs to avoid the collapse of the Tube well. The sedimentary tube wells are drilled up to a depth of 30m to 300m depending on the area, yield,etc. In alluvial formations, the hand rotary used for drilling tube wells ranges from 10m to 15m. In river beds, infiltration tube wells used for extraction of groundwater.

In Hard rock, the well designing is simple. The upper top soil and highly weathered zone is cased with PVC pipe and the remaining weathered, Fissured, Jointed portion is left as it is. In Villupuram District, the weathered zone ranges from 1.0m to 12.0m. In Granitic gneiss area, the highly weathered portion will be more up to 15m but in charnockite area, the weathered zone will extend up to 8.0m to 10.m only. In Sedimentary area, the well construction depends on the occurrence of sand thickness in the referred area. The logger is also used in the construction to identify the area of good quality of water.

2. GROUNDWATER REGIME MONITORING:

(i) Notes on existing water level scenario:

The water level is being monitored by State Ground & Surface Water Resources Data Centre from 1971 onwards from a network of 1746 observation wells (shallow open wells) located all over the State. The water level readings are observed in the first week of every month by the field officers. In Dharmapuri District, 184 observation wells and 48 piezometers, totally 232 wells are monitoring on Monthly basis. The Central Ground Water Board also monitors the water level from 900 numbers of wells spread all over the State. They observe water level four times in a year. (i.e January, May, August and November). The collected water level data are uploaded in GWDES software and database is maintained regularly for analysing the water level trend with rainfall. From the Monitoring network of wells, the selected representative wells are taken for Resource Estimation computations.

In Dharmapuri District, during the pre monsoon, the water level generally in declining trend ranges from G.L. to 15m. The depth of well below GroundLevel 12.0m are become dry during hot season like May, June, July. In the post monsoon, the water level generally in upward trend due to rainfall and it may reach the Ground Level also. The water level trend maps for pre and post monsoons are included as Annexure- I & II.

(ii) Long term trend of water level:

The long term fluctuations of water levels range from G.L. to 14.0m in many parts of the Dharmapuri District. The analysis reveals that the water level has gone down in the north, west and central parts of the Dharmapuri District. The

inference taken from the annual fluctuation is due to lack of rainfall which in turn affects the groundwater levels in phreatic aquifer. The seasonal fluctuation study reveals that due to necessity for development of ground water for different sector needs and due to failure of monsoons, the water level has gone down. The hydrograph of observation wells water level trend from 2005 to 2017 enclosed as Annexure – III and water level trend from 2000 to 2017 of Piezometers enclosed as Annexure – IV for Dharmapuri District.

(iii) Existing network of Monitoring wells:

In Dharmapuri District, the existing network of monitoring wells is 232 wells, 184 wells are observation wells and 48 wells are piezometers. These wells are observed for every month water level.

Dharmapuri District: Observation Wells - Location and Co-ordinates

Well No	District	Tahsil / Taluk	Block / Mandal	Village	Latitude	Longitude
53002	Dharmapuri	Harur	Pappireddipatti	Menasi	11°58'00"	78°20'00"
53003	Dharmapuri	Dharmapuri	Nallampalli	Thoppur	11°56'00"	78°04'00"
53004A	Dharmapuri	Pennagaram	Pennagaram	Perumbalai	11°57'00"	77°57'00"
53005	Dharmapuri	Harur	Harur	Mullaivanam	12°06'00"	78°38'00"
53006	Dharmapuri	Harur	Harur	K.Vetrapatti	12°07'00"	78°29'05"
53007	Dharmapuri	Harur	Morappur	Gopinathampatti	12°08'00"	78°21'00"
53008A	Dharmapuri	Dharmapuri	Dharmapuri	Solaikottai	12°08'00"	78°13'00"
53009	Dharmapuri	Dharmapuri	Nallampalli	B.S. Agraharam	12°08'38"	78°02'42"
53010	Dharmapuri	Pennagaram	Pennagaram	Kottaiyur	12°07'00"	77°54'00"
53014	Dharmapuri	Palacode	Palacode	Periyampatti	12°15'00"	78°11'00"
53014A	Dharmapuri	Uthangarai		Uthangarai	12°15'59"	78°32'09"
53015	Dharmapuri	Palacode	Mathur	Erranahali	12°17'00"	78°04'00"

53019	Dharmapuri	Palacode	Karimangalam	Periyathobai	12°25'00"	78°02'00"
53031	Dharmapuri	Pappireddipatti	Pappireddipatti	Pappireddipatty	11°54'30"	78°22'30"
53031A	Dharmapuri	Pappireddipatti	Pappireddipatti	Pappireddipatty	11°54'30"	78°22'30"
53031AY	Dharmapuri	Pappireddipatti	Pappireddipatti	Pappireddipatty	11°54'30"	78°22'30"
53032	Dharmapuri	Pappireddipatti	Pappireddipatti	Bommidi	11°59'00"	78°50'30"
53033	Dharmapuri	Harur	Harur	Kottapatti	11°59'00"	78°41'00"
53034	Dharmapuri	Harur	Harur	Harur	12°03'45"	78°28'04"
53035	Dharmapuri	Harur	Morappur	Morappur	12°07'00"	78°23'40"
53036	Dharmapuri	Harur	Pappireddipatti	Kadathur	12°05'10"	78°17'30"
53036A	Dharmapuri	Pappireddipatti	Morappur	Kadathur	12°05'10"	78°17'30"
53037	Dharmapuri	Harur	Morappur	Kambainallur	12°12'00"	78°19'00"
53038	Dharmapuri	Palacode	Karimangalam	Karimangalam	12°18'30"	78°12'30"
53047	Dharmapuri	Dharmapuri	Nallampalli	Narthampatty	12°02'88"	78°07'58"
53048	Dharmapuri	Dharmapuri	Dharmapuri	Kumarasampattai	12°08'13"	78°09'10"
53049	Dharmapuri	Palacode	Karimangalam	Pulikarai	12°13'45"	78°06'40"
53050	Dharmapuri	Pennagaram	Pennagaram	Papparapatti	12°11'25"	78°02'40"
53050(Ay)	Dharmapuri	Pennagaram	Pennagaram	Papparapatti	12°11'25"	78°02'40"
53051A	Dharmapuri	Pennagaram	Pennagaram	Nagadasampatty	12°06'20"	77°59'40"
53052	Dharmapuri	Pennagaram	Pennagaram	Pennagaram	12°07'30"	77°54'35"
53053	Dharmapuri	Dharmapuri	Dharmapuri	Krishnapuram	12°12'35"	78°14'15"
53053A	Dharmapuri	Dharmapuri	Dharmapuri	Krishnapuram	12°12'12"	78°44'30"
53054	Dharmapuri	Palacode	Karimangalam	Hanumanthapuram	12°19'50"	78°09'20"

53055	Dharmapuri	Palacode	Palacode	Marandahalli	12°22'45"	78°01'20"
53056	Dharmapuri	Palacode	Palacode	Sengodipatti	12°19'52"	78°01'55"
53057	Dharmapuri	Harur	Harur	Sittiling	11°54'00"	78°38'00"
53058	Dharmapuri	Pappireddipatti	Pappireddipatti	Salur	11°56'00"	78°26'00"
53058A	Dharmapuri	Pappireddipatti	Pappireddipatti	Salur	11°56'00"	78°26'00"
53059A	Dharmapuri	Pappireddipatti	Morappur	Sungarahalli	12°03'00"	78°15'00"
53060	Dharmapuri	Harur	Harur	Bairanaickanpatt y	12°02'00"	78°40'00"
53061	Dharmapuri	Harur	Harur	Chettipatti	11°59'00"	78°27'00"
53062	Dharmapuri	Harur	Morappur	Beddur	12°04'00"	78°25'00"
53069	Dharmapuri	Palacode	Karimangalam	Vellichandai	12°21'00"	78°05'00"
53080	Dharmapuri	Harur	Harur	Valaithottam	11°58'50"	78°32'39"
53081	Dharmapuri	Harur		Vallimadurai	11°58'30"	78°32'22"
A53001	Dharmapuri	Dharmapuri	Dharmapuri	Pidamaneri	12°07'41"	78°08'49"
A53002	Dharmapuri	Dharmapuri	Dharmapuri	Weaver's Colony	12°07'49"	78°09'27"
A53003	Dharmapuri	Dharmapuri	Dharmapuri	Madikonpalaya m	-	-
A53004	Dharmapuri	Dharmapuri	Dharmapuri	7th Day School	12°06'20"	78°08'58"
A53005	Dharmapuri	Dharmapuri	Dharmapuri	Salaivinayagar Koil	12°07'43"	78°09'50"
A53007	Dharmapuri	Harur	Harur	Opp.to Dass Theatre	-	-
A53008	Dharmapuri	Dharmapuri	Dharmapuri	Old Hospital	12°06'23"	78°08'10"
A53009	Dharmapuri	Harur	Harur	Taluk Office (Bdo)	12°07'41"	78°09'48"
A53010	Dharmapuri	Harur	Harur	Police Quarters	12°06'59"	78°08'48"
A53015	Dharmapuri	Pennagaram	Pennagaram	Dasampatty Road	12°14'42"	78°25'42"

A53016	Dharmapuri	Pennagaram	Pennagaram	Vet. Hospital	12°19'19"	78°03'38"
A53017	Dharmapuri	Pennagaram	Pennagaram	Harijan's Colony	13°00'0"	80°06'41"
A53018	Dharmapuri	Pennagaram	Pennagaram	Taluk Office	12°07'49"	78°09'41"
A53019	Dharmapuri	Palacode	Palacode	B.d.o,'s Office	12°08'00"	77°53'48"
A53020	Dharmapuri	Palacode	Palacode	Hosur Road Bridge	12°44'03"	79°49'23"
A53021	Dharmapuri	Palacode	Palacode	Vet. Hospital	12°08'59"	78°31'07"
A53028	Dharmapuri	Denkanikotti	Denkanikottai	Sub-register Office	12°31'32"	77°47'24"
A53032	Dharmapuri	Hosur	Hosur	Hosur- Near Tank	12°43'47"	77°49'37"
MIC D 0001	Dharmapuri	Dharmapuri	Dharmapuri	Konaginaickanalli	12°11'57"	78°11'15"
MIC D 0002	Dharmapuri	Dharmapuri	Dharmapuri	K.naduhalli	12°12'22"	78°12'55"
MIC D 0003	Dharmapuri	Dharmapuri	Dharmapuri	Pulithikarai	12°12'23"	78°16'13"
MIC D 0004	Dharmapuri	Dharmapuri	Dharmapuri	Kondakarahalli	12°00'25"	78°13'55"
MIC D 0005	Dharmapuri	Dharmapuri	Dharmapuri	Veppilaimuthampatti	11°58'52"	78°09'53"
MIC D 0006	Dharmapuri	Dharmapuri	Nallampalli	Kammampatti	11°55'15"	77°57'15"
MIC D 0007	Dharmapuri	Dharmapuri	Nallampalli	Bolanahalli	12°01'45"	78°03'43"
MIC D 0008	Dharmapuri	Dharmapuri	Nallampalli	Maniyathahalli	12°00'05"	78°01'50"
MIC D 0009	Dharmapuri	Dharmapuri	Nallampalli	Elagiri	12°02'00"	78°04'30"
MIC D 0010	Dharmapuri	Dharmapuri	Dharmapuri	Adagapadi	12°08'45"	78°05'21"
MIC D 0011	Dharmapuri	Dharmapuri	Nallampalli	Pangunattam	12°07'56"	78°01'05"
MIC D 0012	Dharmapuri	Dharmapuri	Nallampalli	Errabaiyanahalli	12°05'51"	77°59'17"
MIC D 0013	Dharmapuri	Dharmapuri	Nallampalli	Nagarkudal	12°05'05"	78°03'30"

MIC D 0014	Dharmapuri	Palacode	Palacode	Buganahalli	12°11'30"	78°05'25"
MIC D 0015	Dharmapuri	Palacode	Karimangalam	Naganampatti	12°16'50"	78°11'25"
MIC D 0016	Dharmapuri	Palacode	Karimangalam	Bommahalli	12°18'26"	78°10'04"
MIC D 0017	Dharmapuri	Palacode	Karimangalam	Baisuhalli	12°12'46"	78°11'22"
MIC D 0018	Dharmapuri	Palacode	Karimangalam	Hanumanthapuram	12°19'09"	78°06'59"
MIC D 0019	Dharmapuri	Palacode	Palacode	Chikkardanahalli	12°19'12"	78°05'00"
MIC D 0020	Dharmapuri	Palacode	Palacode	P.Settihali	12°19'30"	78°03'05"
MIC D 0021	Dharmapuri	Palacode	Palacode	Senganbasuvant halav	12°22'31"	78°02'35"
MIC D 0022	Dharmapuri	Palacode	Palacode	Selliyampatti	12°11'10"	78°07'45"
MIC D 0023	Dharmapuri	Palacode	Palacode	Sirenahalli	12°18'08"	77°59'47"
MIC D 0024	Dharmapuri	Palacode	Palacode	Belamaranahalli	12°20'50"	78°00'10"
MIC D 0025	Dharmapuri	Palacode	Palacode	Chinnagoundan ahalli	12°27'33"	77°59'57"
MIC D 0026	Dharmapuri	Palacode	Karimangalam	Jittandahalli	12°29'08"	78°01'29"
MIC D 0027	Dharmapuri	Palacode	Palacode	Panjapalli	12°29'30"	77°57'34"
MIC D 0028	Dharmapuri	Palacode	Karimangalam	Nammandahalli	12°27'52"	77°58'05"
MIC D 0029	Dharmapuri	Palacode	Palacode	Boppadi	12°17'15"	78°01'15"
MIC D 0030	Dharmapuri	Pennagaram	Pennagaram	Panaikulam	12°13'45"	78°03'45"
MIC D 0031	Dharmapuri	Pennagaram	Pennagaram	Kalappampadi	12°02'17"	77°57'06"
MIC D 0032	Dharmapuri	Pennagaram	Pennagaram	Chinnampalli	12°00'39"	77°57'56"
MIC D 0033	Dharmapuri	Pennagaram	Pennagaram	Sathyanathapuram	12°06'27"	77°54'43"
MIC D 0034	Dharmapuri	Pennagaram	Pennagaram	Gendanahalli	11°55'26"	77°55'12"

MIC D 0035	Dharmapuri	Pennagaram	Pennagaram	Badirahalli	11°55'59"	77°52'08"
MIC D 0036	Dharmapuri	Pennagaram	Pennagaram	Sunchalnattam	12°00'01"	77°47'18"
MIC D 0037	Dharmapuri	Pennagaram	Pennagaram	Donnakuttahalli	12°00'04"	77°49'50"
MIC D 0038	Dharmapuri	Pennagaram	Pennagaram	Kodihalli	12°06'17"	77°51'30"
MIC D 0039	Dharmapuri	Pennagaram	Pennagaram	Ajjanahalli	12°03'00"	77°49'30"
MIC D 0040	Dharmapuri	Harur	Harur	Periyapatty	12°05'39"	78°41'17"
MIC D 0041	Dharmapuri	Harur	Harur	Andiyur	12°06'21"	78°36'56"
MIC D 0042	Dharmapuri	Harur	Harur	Doddampatty	12°02'05"	78°28'04"
MIC D 0043	Dharmapuri	Harur	Harur	Kottapatty	11°59'52"	78°40'05"
MIC D 0044	Dharmapuri	Harur	Harur	Sittiling	11°54'44"	78°37'21"
MIC D 0045	Dharmapuri	Harur	Harur	Suranatham	11°58'06"	78°39'36"
MIC D 0046	Dharmapuri	Harur	Harur	Thadampatti	11°53'23"	78°35'24"
MIC D 0047	Dharmapuri	Harur	Harur	Velanur	11°52'21"	78°35'42"
MIC D 0048	Dharmapuri	Harur	Harur	Tambal	12°09'00"	78°37'49"
MIC D 0049	Dharmapuri	Harur	Harur	Poyyapatti	12°07'05"	78°34'10"
MIC D 0050	Dharmapuri	Harur	Harur	Ettiyampatti	12°03'13"	78°32'45"
MIC D 0051	Dharmapuri	Harur	Harur	Sakkilipatti	12°08'31"	78°30'41"
MIC D 0052	Dharmapuri	Harur	Harur	Kongavembu	12°09'05"	78°31'04"
MIC D 0053	Dharmapuri	Harur	Harur	Kilmorappur	12°07'56"	78°27'51"
MIC D 0054	Dharmapuri	Harur	Harur	Kudumiyampatti	12°00'42"	78°30'05"
MIC D 0055	Dharmapuri	Harur	Harur	Achalvadi	12°00'27"	78°29'41"
MIC D 0056	Dharmapuri	Harur	Harur	Keeraipatti	12°01'33"	78°31'14"
MIC D 0057	Dharmapuri	Harur	Harur	Chellampatti	12°05'23"	78°30'50"

MIC D 0058	Dharmapuri	Harur	Morappur	Agraharam	12°11'55"	78°22'21"
MIC D 0059	Dharmapuri	Harur	Morappur	Navalai	12°10'22"	78°21'59"
MIC D 0060	Dharmapuri	Harur	Morappur	Echampadi	12°13'11"	78°21'34"
MIC D 0061	Dharmapuri	Harur	Morappur	Kambainallur	12°12'43"	78°19'44"
MIC D 0062	Dharmapuri	Pappireddipatti	Morappur	Ramiyanahalli	12°02'18"	78°22'45"
MIC D 0063	Dharmapuri	Pappireddipatti	Morappur	Tenkaraikottai	12°00'48"	78°23'46"
MIC D 0064	Dharmapuri	Pappireddipatti	Morappur	Buddireddipatti	12°04'19"	78°17'56"
MIC D 0065	Dharmapuri	Pappireddipatti	Morappur	Kedagarahalli	12°04'53"	78°16'11"
MIC D 0066	Dharmapuri	Pappireddipatti	Morappur	Buddireddipatti	12°03'07"	78°18'12"
MIC D 0067	Dharmapuri	Pappireddipatti	Pappireddipatti	Alapuram	11°58'13"	78°23'44"
MIC D 0068	Dharmapuri	Pappireddipatti	Pappireddipatti	Venkatasamudram	11°55'37"	78°21'02"
MIC D 0069	Dharmapuri	Pappireddipatti	Pappireddipatti	Bairnattam	11°56'44"	78°17'58"
MIC D 0070	Dharmapuri	Pappireddipatti	Pappireddipatti	Pattukonampatti	11°52'43"	78°22'01"
MIC D 0071	Dharmapuri	Pappireddipatti	Pappireddipatti	Adigarapatti	11°56'13"	78°23'31"
MIC D 0072	Dharmapuri	Pappireddipatti	Pappireddipatti	Pudupatti	11°58'00"	78°24'58"
MIC K0001	Dharmapuri	Denkanikotti	Kelamangalam	Biddireddy	12°38'58"	77°49'44"
MIC K0002	Dharmapuri	Denkanikotti	Thalli	Vanamangalam	12°36'47"	77°45'43"
MIC K0003	Dharmapuri	Denkanikotti	Thalli	Thalikothanur	12°34'41"	77°41'13"
MIC K0004	Dharmapuri	Denkanikotti	Thalli	Marupalli	12°33'19"	77°38'34"
MIC K0005	Dharmapuri	Denkanikotti	Thalli	Thalli	12°35'05"	77°39'45"
MIC K0006	Dharmapuri	Denkanikotti	Thalli	Ballaplli	12°32'38"	77°42'41"
MIC K0007	Dharmapuri	Denkanikotti	Thalli	Kakkadasam	12°34'04"	77°43'27"
MIC K0008	Dharmapuri	Denkanikotti	Thalli	Anchetty	12°21'18"	77°42'54"

MIC K0009	Dharmapuri	Denkanikotti	Thalli	Kongchettihalli	12°27'28"	77°45'14"
MIC K0010	Dharmapuri	Denkanikotti	Thalli	Gollapalli	12°30'31"	77°42'53"
MIC K0011	Dharmapuri	Denkanikotti	Thalli	Baladoddanapalli	12°30'31"	77°42'29"
MIC K0012	Dharmapuri	Denkanikotti	Thalli	Kottaiyur	12°17'12"	77°37'20"
MIC K0013	Dharmapuri	Denkanikotti	Thalli	Gumalapuram	12°39'23"	77°39'48"
MIC K0015	Dharmapuri	Hosur	Shoolagiri	Thiyagarasanapalli	12°38'30"	78°05'30"
MIC K0016	Dharmapuri	Hosur	Shoolagiri	Marandapalli	12°42'34"	78°02'28"
MIC K0017	Dharmapuri	Hosur	Hosur	Thuppuganapalli	12°37'35"	78°55'34"
MIC K0018	Dharmapuri	Hosur	Shoolagiri	Uddanapalli	12°36'55"	77°56'21"
MIC K0019	Dharmapuri	Hosur	Shoolagiri	Halesibam	12°35'36"	77°58'02"
MIC K0020	Dharmapuri	Hosur	Hosur	Kelavarapalli	12°46'16"	77°52'35"
MIC K0021	Dharmapuri	Hosur	Hosur	Nallur	12°47'18"	77°49'46"
MIC K0022	Dharmapuri	Krishnagiri	Barugur	Sigaralahalli	12°30'18"	78°23'30"
MIC K0023	Dharmapuri	Krishnagiri	Barugur	Oppadavadi	12°38'55"	78°23'58"
MIC K0024	Dharmapuri	Krishnagiri	Barugur	Neralakottai	12°33'52"	78°22'07"
MIC K0025	Dharmapuri	Krishnagiri	Barugur	Chinnamatrapalli	12°37'27"	78°19'31"
MIC K0026	Dharmapuri	Krishnagiri	Barugur	Achamangalam	12°31'10"	78°20'00"
MIC K0027	Dharmapuri	Krishnagiri	Barugur	Madepalli	12°32'48"	78°20'17"
MIC K0028	Dharmapuri	Krishnagiri	Barugur	Anjur	12°29'28"	78°17'49"
MIC K0029	Dharmapuri	Krishnagiri	Barugur	Kammapalli	12°33'48"	78°16'04"
MIC K0030	Dharmapuri	Krishnagiri	Kaveripattinam	Barur	12°17'40"	78°18'35"
MIC K0031	Dharmapuri	Krishnagiri	Kaveripattinam	Timmapuram	12°26'45"	78°31'10"
MIC K0032	Dharmapuri	Krishnagiri	Kaveripattinam	Jagadab	12°22'22"	78°12'55"

MIC K0033	Dharmapuri	Krishnagiri	Krishnagiri	Byanapalli	12°33'14"	78°10'54"
MIC K0034	Dharmapuri	Krishnagiri	Krishnagiri	Chikkapoovathi	12°30'10"	78°04'21"
MIC K0035	Dharmapuri	Krishnagiri	Krishnagiri	Agaram	12°31'27"	78°07'31"
MIC K0036	Dharmapuri	Krishnagiri	Krishnagiri	Alapatti	12°30'06"	78°06'17"
MIC K0037	Dharmapuri	Krishnagiri	Krishnagiri	Kattiganapalli	12°30'40"	78°12'50"
MIC K0038	Dharmapuri	Krishnagiri	Krishnagiri	Beemandapalli	12°37'33"	78°07'46"
MIC K0039	Dharmapuri	Krishnagiri	Veppanapalli	Gurubarapalli	12°36'14"	78°07'41"
MIC K0040	Dharmapuri	Krishnagiri	Veppanapalli	Madhepalli	12°39'42"	78°10'24"
MIC K0041	Dharmapuri	Krishnagiri	Veppanapalli	Kathiripalli	12°41'58"	78°09'30"
MIC K0042	Dharmapuri	Krishnagiri	Veppanapalli	Nallur	12°44'12"	78°05'25"
MIC K0043	Dharmapuri	Krishnagiri	Veppanapalli	Etrapalli	12°42'41"	78°07'50"
MIC K0044	Dharmapuri	Pochampalli	Kaveripattinam	Jambukuttapatti	12°19'57"	78°21'32"
MIC K0045	Dharmapuri	Pochampalli	Kaveripattinam	Veeramalai	12°20'50"	78°17'47"
MIC K0046	Dharmapuri	Pochampalli	Mathur	Parandapalli	12°17'15"	78°22'18"
MIC K0047	Dharmapuri	Uthangarai	Uthangarai	Nayakanur	12°13'55"	78°37'35"
MIC K0048	Dharmapuri	Uthangarai	Uthangarai	Mittapalli	12°15'31"	78°35'13"
MIC K0049	Dharmapuri	Uthangarai	Uthangarai	Venkatadhampatti	12°16'09"	78°30'53"
MIC K0050	Dharmapuri	Uthangarai	Uthangarai	Kilmathur	12°21'23"	78°34'17"
MIC K0051	Dharmapuri	Uthangarai	Uthangarai	Umaiyanur	12°20'52"	78°32'24"
MIC K0053	Dharmapuri	Uthangarai	Uthangarai	Battalapalli	12°27'40"	78°23'30"
MIC K0054	Dharmapuri	Uthangarai	Uthangarai	Nagampatti	12°24'09"	78°24'13"
MIC K0055	Dharmapuri	Uthangarai	Uthangarai	Mungileri	12°12'05"	78°30'32"
MIC K0056	Dharmapuri	Uthangarai	Uthangarai	Thaneerpanthal	12°12'47"	78°32'35"

Dharmapuri District- Piezometers - Location and Co-ordinates

Well no	District	Tashil/Taluk	Block/Mandal	Village	Latitude	Longitude
HP 31572	Cuddalore	Cuddalore	Cuddalore	Periakattuppalayam	11.853889	79.79
HP31515	Cuddalore	Thittakudi	Mangalore	Vallimarudham	11.508889	78.944722
HP31516A	Cuddalore	Thittakudi	Mangalore	Kaludur	11.506111	79.093056
HP31538	Cuddalore	Vriddhachalam	Vriddhachalam	T.mavadandal	11.628056	79.218611
HP31539	Cuddalore	Vriddhachalam	Vriddhachalam	M.Parur	11.580833	79.254722
HP31540	Cuddalore	Vriddhachalam	Nallur	Vilambavur	11.543889	79.075278
HP31542	Cuddalore	Thittakudi	Mangalore	Eluthur	11.438333	79.0125
HP31543A	Cuddalore	Vriddhachalam	Nallur	Veppur	11.528333	79.123056
HP31544	Cuddalore	Vriddhachalam	Vriddhachalam	Keelpalaiyur	11.466111	79.4225
HP31545	Cuddalore	Vriddhachalam	Kammapuram	Kammapuram	11.478333	79.421667
HP31546	Cuddalore	Chidambaram	Parangippettai	Puduchathiram	11.542222	79.722778
HP31547	Cuddalore	Kattumannarkoil	Kumaratchi	Kumaratchi	11.310556	79.629167
HP31548	Cuddalore	Kattumannarkoil	Kattumannarkoil	Lalpet	11.298611	79.549167
HP31549	Cuddalore	Cuddalore	Cuddalore	Thiruvandipuram	11.750556	79.711944
HP31551	Cuddalore	Panruti	Annagramam	Anna Grammam	11.788056	79.601944
HP31552	Cuddalore	Cuddalore	Cuddalore	Cuddalore - OT	11.722222	79.774722
HP31553A	Cuddalore	Vriddhachalam	Kammapuram	V.Kumaramangalam	11.491667	79.385556
HP31554	Cuddalore	Panruti	Annagramam	Palur	11.758333	79.628889
HP31558	Cuddalore	Kattumannarkoil	Kattumannarkoil	Eyyalur	11.188056	79.515833
HP31559	Cuddalore	Chidambaram	Keerapalayam	Palayamkottai . I.	11.358611	79.473889
HP31560A	Cuddalore	Kattumannarkoil	Kattumannarkoil	Kondasamuthram	11.337222	79.474722
HP31575	Cuddalore	Chidambaram	Kumaratchi	Chidambaram	11.393056	79.6925
HP31577	Cuddalore	Cuddalore	Cuddalore	Thukkanampakkam	11.841667	79.706944
HP31578	Cuddalore	Kurinjipadi	Kurinjipadi	Ramanathankuppam	11.623889	79.693056
HP31580	Cuddalore	Kurinjipadi	Kurinjipadi	Vadalur	11.554444	79.546389
HP31581	Cuddalore	Vriddhachalam	Vriddhachalam	Ko-poovanur	11.610833	79.306389
INV 11228	Cuddalore	Thittakudi	Mangalore	Lekkur	11.465833	79.018611
INV 31436	Cuddalore	Cuddalore	Cuddalore	Cuddalore N.T	11.756667	79.761111
INV 31445	Cuddalore	Vriddhachalam	Vriddhachalam	Vriddhachalam	11.506944	79.3275
INV 31446	Cuddalore	Thittakudi	Nallur	Pennadam	11.404167	79.250556
INV 31461	Cuddalore	Vriddhachalam	Kammapuram	Melakupam	11.570833	79.439722
INV31434	Cuddalore	Panruti	Panruti	Poongunam	11.788889	79.797222
INV31435	Cuddalore	Cuddalore	Cuddalore	Vandarasankuppam	11.722222	79.634722
INV31446	Cuddalore	Chidambaram	Kumaratchi	Keerapalayam	11.431944	79.653333
INV31447	Cuddalore	Chidambaram	Melbhuvanagiri	Krishnapuram	11.484722	79.616667
INV31448	Cuddalore	Chidambaram	Keerapalayam	Mazhavarayanallur	11.4175	79.520556
INV31449	Cuddalore	Kattumannarkoil	Kattumannarkoil	Parivilagam	11.3425	79.603611
INV31452	Cuddalore	Kurinjipadi	Kurinjipadi	Pethanaickenkuppam	11.584167	79.615833
INV31453	Cuddalore	Kurinjipadi	Kurinjipadi	Kattiyankuppam	11.637222	79.633056
INV31454	Cuddalore	Chidambaram	Keerapalayam	Pudaiyur	11.361667	79.515556

INV31455	Cuddalore	Chidambaram	Keerapalayam	Koodalaiyathur	11.415278	79.470278
INV31456	Cuddalore	Chidambaram	Kumaratchi	Thuniseramedu	11.376389	79.655278
INV31457	Cuddalore	Chidambaram	Melbhuvanagiri	Kiliyanur	11.424722	79.590278
INV31462	Cuddalore	Thittakudi	Mangalore	Alambadi	11.459444	79.061389
INV31463	Cuddalore	Thittakudi	Mangalore	Vinayaganandal	11.518056	79.04
MWS 31582	Cuddalore	Panruti	Panruti	Marungur	11.655	79.535278
MWS 31585	Cuddalore	Panruti	Panruti	Thiruvamur	11.768056	79.478333

(iv) Data Constraints:

The following are constraints in collecting the water level data in the field and validating the data are:

- 1) The water level data are collected on the monthly basis in the referred observation wells and piezometers. The collected data is not sufficient quantity for analyzing purpose due to drying of wells, Wells abounded by various reasons, lack of selecting the alternate wells, lack of open wells available for monitoring purpose due to increased usage of bore wells in the villages, Panchayats, etc. In many villages, the water supply schemes implemented by overhead tank supply or mini energised pumps and the existing open wells are not used generally by the villagers and moreover, they filled with garbage.
- 2) The number of bore wells should be increased for monitoring purpose.
- 3) The site selection of new bore wells should be based on the Geological methods.
- 4) Strengthening the network of monitoring wells by closing the gaps in the network.
- 5) Maintenance cost should be allotted to maintain the bore wells on the periodical basis to maintain the quality as well as yield.
- 6) Installation of Automatic water level recorders in the sensitive and more water level fluctuation in the bore wells will helpful to monitor the extensive depletion of groundwater areas.
- 7) Upgrading the measuring instruments will helpful to take accurate reading of water levels in the field.
- 8) Upgrading the soft ware will helpful to minimize the errors and increasing the accuracy of data.

9) Erecting the Telemetric water level recorders in the over exploited Firkas will helpful to monitor the over extraction of groundwater.

10) Lack of manpower and transporting vehicles are also major problems for data collection in the field in proper time.

3. DYNAMIC GROUND WATER RESOURCES:

The State Ground and Surface Water Resources Data Centre has estimated the ground water resources of Tamil Nadu periodically in co-ordination with the Central Ground Water Board, Government of India , Ministry of Water Resources, Chennai, based on the Methodology evolved by the Ground Water Resources Estimation Committee, 1997 (GEC 97).

Groundwater potential assessment is a dynamic one and not static. While assessing an area, the following factors can be considered such as Geology, Total Irrigated Area, Total Number of Wells used for Irrigation, Water Level Data for the past five years, Average Rainfall, Total Recharge, Irrigation methods adopted in the area, Cropping pattern details, Seepage factor, Specific yield, Geological conditions prevailing in that area, Recharge through Artificial recharge structures, etc.

Groundwater potential assessment proposal should be presented for approval in the Central and State Level Working Group Committees and then, presented for final approval in the Central Level Committee as well as State Level Committees.

The Ground Water Potential Assessments as on January 1992 and January 1997 were done in the State, taking the Panchayat Union Block as an Assessment Unit and the entire State **was categorized as Dark, Grey and White areas**. The Blocks with more than 85% to 100% ground water development (extraction) were categorized as “Dark Blocks” and the blocks with ground water development between 65% to 85% were categorized as “Grey Blocks” and blocks with less than 65% ground water development were categorized as “White Blocks”.

Subsequently, the **Ground Water Potential Assessment was done as on March 2003 and as on March 2009**. In these assessments, the

Panchayat Union Blocks in Tamil Nadu were **categorized as Over-Exploited, Critical, Semi-Critical, Safe and Saline instead of Dark, Grey and White blocks.** The Blocks with more than 100% extraction were categorized as “Over Exploited Blocks”, the blocks with 90% to 100% extraction as “Critical Blocks”, the blocks with 65% to 90% extraction as “Semi Critical Blocks”, the blocks with less than 65% extraction as “Safe Blocks” and the bad quality blocks were categorized as “Saline Blocks”. No schemes should be formulated in over exploited and critical blocks - “Notified Blocks – A category – (Stage of Groundwater extraction is 90% and above)”.

The re-estimation of groundwater resources in the State as on March 2011 and as on March 2013 can be assessed in Micro Level basis. In these assessments, the assessing unit is Firka (Unit of Taluk) and **categorized as Over-Exploited, Critical, Semi-Critical, Safe, and Saline Firkas.** As on March 2013 assessment, in the Dharmapuri District

Based on the Estimation of Ground Water Resources of Tamil Nadu State as on March 2013, Out of 1139 Firkas in the State, 358 Firkas are categorized as “Over Exploited Firkas”, 105 Firkas are categorized as “Critical Firkas”, 212 Firkas are categorized as “Semi Critical Firkas”, 429 Firkas are categorized as “Safe Firkas” and 35 Firkas are categorized as “Saline Firkas”.

When compared to last assessment as on March 2011, the “Over Exploited Firkas” comes down from 374 to 358 Firkas, the “Critical Firkas” increased from 48 to 105 Firkas, the “Semi Critical Firkas” comes down marginally from 235 to 212 Firkas, the “Safe Firkas” comes down marginally from 437 to 429 Firkas and the “Saline Firkas” remains same as 35 Firkas. The alteration of Firkas are due to the construction of Artificial Recharge structures such as Check Dams, Recharge Wells, Recharge shafts, percolation ponds; etc was constructed in the “Over Exploited Firkas” by various departments.

Methodology adopted for Estimation of Ground Water Potential :

The present methodology used for resources assessment is known as Ground Water Resource Estimation Methodology - 1997 (GEC'97) .In GEC'97, two approaches are recommended - **water level fluctuation method and norms of rainfall infiltration method.** The water level fluctuation method is based

on the concept of storage change due to differences between various input and output components. Input refers to recharge from rainfall and other sources and subsurface inflow into the unit of assessment. Output refers to ground water draft, ground water evapotranspiration, base flow to streams and subsurface outflow from the unit. Since the data on subsurface inflow / outflow are not readily available, it is advantageous to adopt the unit for ground water assessment as basin / sub basin / watershed, as the inflow / outflow across these boundaries may be taken as negligible.

In each assessment unit, hilly areas having slope more than 20% are deleted from the total area to get the area suitable for recharge. Further, areas where the quality of ground water is beyond the usable limits should be identified and handled separately. The remaining area after deleting the hilly area and separating the area with poor ground water quality is to be delineated into command and non-command areas. Ground water assessment in command and non-command areas are done separately for monsoon and non-monsoon seasons.

The rainfall recharge during monsoon season computed by Water Level Fluctuation (WLF) method is compared with recharge figures from Rainfall Infiltration Factor (RIF) method. In case the difference between the two sets of data are more than 20% then RIF figure is considered, otherwise monsoon recharge from WLF is adopted. While adopting the rainfall recharge figures, weight age is to be given to WLF method over adhoc norms method of RIF. Hence, wherever the difference between RIF & WLF is more than 20%, data have to be scrutinized and corrected accordingly.

During non-Monsoon season, rainfall recharge is computed by using Rainfall infiltration Factor (RIF) method. Recharge from other sources is then added to get total non-Monsoon recharge. In case of areas receiving less than 10% of the annual rainfall during non-monsoon season, the rainfall recharge is ignored.

The total annual ground water recharge of the area is the sum-total of monsoon and non-monsoon recharge. An allowance is kept for natural discharge in the non-monsoon season by deducting 5 to 10 % of total annual ground water recharge.

The balance ground water available accounts for existing ground water withdrawal for various uses and potential for future development. This quantity is termed as Net Ground Water Availability.

Net Ground Water Availability = Annual Ground Water Recharge - Natural discharge during non-monsoon season.

GEC'97 methodology has recommended norms for various parameters being used in ground water recharge estimation. These norms vary depending upon water bearing formations and agroclimatic conditions. While norms for specific yield and recharge from rainfall values are to be adopted within the guidelines of GEC'97, in case of other parameters like seepage from canals, return flow from irrigation, recharge from tanks & ponds, water conservation structures, results of specific case studies may replace the adhoc norms.

The Gross yearly ground water draft is to be calculated for Irrigation, Domestic and Industrial uses. The gross ground water draft would include the ground water extraction from all existing ground water structures during monsoon as well as during non-monsoon period. While the number of ground water structures should preferably be based on latest well census, the average unit draft from different types of structures should be based on specific studies or adhoc norms given in GEC'97 report.

The stage of Ground water Development is defined by

$$\text{Stage of Ground water Development (\%)} = \frac{\text{Existing Gross Ground water Draft for all uses}}{\text{Net annual Ground Water Availability}} \times 100$$

The units of assessment are categorized for ground water development based on two criteria – a) stage of ground water development and b) long-term trend of pre and post monsoon water levels. Four categories are - Safe areas which have ground water potential for development; Semi-critical areas where cautious ground water development is recommended; Critical areas; Over -exploited areas where there should be intensive monitoring and evaluation and future ground water development be linked with water conservation measures.

The criteria for categorization of assessment units are as follows:

S. No.	Stage of Groundwater Development	Significant Long term Decline		Categorization
		Pre-monsoon	Post -monsoon	
1.	<=70%	No	No	SAFE
		Yes / No	No / Yes	To be re-assessed
		Yes	Yes	To be re-assessed
2.	>70% and <=90%	No	No	To be re-assessed
		Yes / No	No / Yes	SEMI – CRITICAL
		Yes	Yes	SEMI – CRITICAL
3.	>90 and <=100%	No	No	To be re-assessed
		Yes / No	No / Yes	CRITICAL
		Yes	Yes	CRITICAL
4.	>100%	No	No	To be re-assessed
		Yes / No	No / Yes	OVER- EXPLOITED
		Yes	Yes	OVER- EXPLOITED

Note: 'To be re-assessed' means that data is to be checked and reviewed. If the ground water resources assessment and the trend of long term water levels contradict each other. This anomalous situations requires a review of the ground water resource computations, as well as the reliability of water level data.

The long term ground water level data should preferably be for a period of 10 years. The significant water level decline may be taken in consideration between 10 to 20 cm/ year depending upon the local hydro geological conditions.

Dynamic Ground Water Resources Estimation of TamilNadu As on March 2013

District Summary

(in ha.m)

DHARMAPURI DISTRICT							
Sl.No (District)	District	Net Annual Ground Water Availability	Existing Gross Ground Water Draft for Irrigation	Existing Gross Ground Water Draft for domestic and industrial water supply	Existing Gross Ground Water Draft for All uses (4+5)	Stage of Ground Water Development $\{(6/3)*100\}$ %	No of Over Exploited Firkas
1	2	3	4	5	6	7	8
1	DHARMAPURI	36,669.66	45,262.44	1,903.07	47,165.51	129	14

Firka Wise Summary

(in ha.m)

Sl.No	Assessment Unit (Firka)	Net Annual Ground Water Availability	Existing Gross Ground Water Draft for Irrigation	Existing Gross Ground Water Draft for domestic and industrial water supply	Existing Gross Ground Water Draft for All uses (4+5)	Stage of Ground Water Development $\{(6/3)*100\}$ %	Category of the Firka
1	BOMMIDI	2,076.75	2,944.35	93.72	3,038.07	146	OVER EXPLOITED
2	DHARMAPURI	1,766.57	1,326.74	144.66	1,471.40	83	SEMI CRITICAL
3	HARUR	2,559.54	2,097.85	92.44	2,190.29	86	SEMI CRITICAL
4	INDUR	1,145.81	1,954.63	81.74	2,036.37	178	OVER EXPLOITED
5	KADATHUR	1,477.86	2,287.48	48.76	2,336.24	158	OVER EXPLOITED
6	KAMBAINALLUR	1,462.55	1,931.38	49.66	1,981.03	135	OVER EXPLOITED
7	KARIMANGALAM	1,822.48	3,836.10	89.36	3,925.46	215	OVER EXPLOITED

DHARMAPURI DISTRICT							
Sl.No	Assessment Unit (Firka)	Net Annual Ground Water Availability	Existing Gross Ground Water Draft for Irrigation	Existing Gross Ground Water Draft for domestic and industrial water supply	Existing Gross Ground Water Draft for All uses (4+5)	Stage of Ground Water Development $\{(6/3)*100\}$ %	Category of the Firka
8	KRISHNAPURAM	1,610.37	1,260.60	66.54	1,327.14	82	SEMI CRITICAL
9	MARANDAHALLI	1,254.49	2,373.80	53.56	2,427.36	193	OVER EXPLOITED
10	MORAPPUR	1,825.94	1,612.00	72.72	1,684.72	92	CRITICAL
11	NALLAMPALLI	1,053.62	882.65	90.31	972.96	92	CRITICAL
12	PALACODE	2,254.79	3,108.45	89.34	3,197.79	142	OVER EXPLOITED
13	PALAYAM	1,081.78	1,862.75	75.32	1,938.07	179	OVER EXPLOITED
14	PAPPARAPATTY	1,336.59	1,719.38	84.13	1,803.51	135	OVER EXPLOITED
15	PAPPIREDDIPATTY	1,924.14	1,633.24	141.16	1,774.40	92	CRITICAL
16	PENNAGARAM	1,228.23	1,983.00	75.01	2,058.01	168	OVER EXPLOITED
17	PERUMBALAI	551.14	1,077.80	45.37	1,123.16	204	OVER EXPLOITED
18	PULIKARAI	2,051.25	3,313.00	75.74	3,388.74	165	OVER EXPLOITED
19	SUNJALNATHAM	1,135.36	862.89	54.37	917.26	81	SEMI CRITICAL
20	THEERTHAMALAI	3,850.68	2,875.75	197.58	3,073.33	80	SEMI CRITICAL
21	THENKARAIKOTTAI	1,648.41	2,521.10	89.92	2,611.02	158	OVER EXPLOITED
22	VELLICHANDAI	1,551.30	1,797.53	91.66	1,889.19	122	OVER EXPLOITED
TOTAL		36,669.66	45,262.44	1,903.07	47,165.51	129	

4. Groundwater quality issues:

The rainfall is the main source for the availability of water both in surface and sub surface. The quantum of rainfall varies every year depending upon the monsoon. However, the extraction of surface and sub surface water is increasing year by year. It leads to environmental impact on the water sources like depletion of water level, deterioration of water quality. It makes the demand for the quantification of available water and also its quality for various purposes like agriculture, industries, drinking and domestic purposes.

For the present assessment, the value of Total Dissolved Solids (TDS) have been considered for demarcation of good / bad quality areas. For this purpose, the TDS value of less than or equal to 2000 mg/l have been considered as good quality and the value more than 2000 mg/l have been considered as bad quality areas.

The presence of fluoride in natural Ground Water is having its merits and demerits depending upon the concentration. Presence of fluoride <1.0 mg/l in drinking water reduces dental diseases whereas higher level > 1.50 mg/l will affect the health and causes dental fluoridise. Nitrate is noted significantly in Ground Water due to use of chemical fertilizer for agriculture and other local pollution rocks and soils are also contributing nitrate to Ground Water. Arsenic is another poisonous heavy metal in Ground Water. The allowable limits for drinking purposes are 0.05 mg/l.

In Dharmapuri District, the quality of Ground Water generally ranges from moderate to good quality both in the shallow dug well and bore wells except in & around the Kazhuveli tank, where the water quality is poor due to seawater intrusion in the lagoons during high tide seasons, the production of salt and Aquaculture farming.

5. Groundwater issues and challenges:

The groundwater quantity and quality are to be highlighted and may be analyzed in terms of :

(i)Problems posed by nature:

In terms of Quantitative aspects, nowadays, rainfall may more within the short period of duration. Due to this aspect, recharge is less and runoff will be more. The availability of groundwater is less due to over extraction than recharge. The Percentage of OE/Critical Firkas increased due to this reason. Increasing the artificial recharge structures in the proper areas may avoid the depletion of groundwater especially in OE/Critical Firkas.

(ii) Problems caused by anthropogenic activities:

The problems caused due to intensive groundwater extraction, intensive surface water irrigation, intensive mining activities, growing urban complexes and industrial establishments will lead to drastic depletion in groundwater resources only. Proper alternative recharge structures must be established.

(iii) Problems caused by socio-economic condition:

The land holdings of farmers may be different from another. One farmer having more than 5 Acres has less expense than a farmer having one acre. The free electric supply to all farmers have chance to extract more groundwater. To avoid this, proper guidance will be given to the farmers for the usage of groundwater.

(iv) Administrative issues:

To control, regulate and manage the Ground Water Resources in the State, there is no groundwater act, now in force. But, the **Chennai Metropolitan Area Ground Water (Regulation) Act, 1987** is in force and it extends to Chennai City and notified 302 revenue villages in Kanchipuram and Thiruvallur Districts, only.

The rest of Tamilnadu, **G.O.(Ms).No.142, Public Works (R2) Department, dated: 23.07.2014** and **G.O.(Ms).No.113, Public Works (R2) Dept , Dt:09.06.2016** are regulate and manage the groundwater resources. The Government of Tamil Nadu had enacted the **Tamil Nadu Ground Water (Development and Management) Act, 2003**. However, this **Act was repealed on 14.09.2013**, in order to enact a comprehensive law to develop and manage the groundwater in the changed scenario in the State.

The pricing policy for groundwater users is also an important strategy in controlling the illegal extraction of groundwater by taking from lorries,etc. The unused dug wells and bore wells can be used as artificial recharge structures will be good concept in recharging the ground water.

6. Groundwater Management and Regulations:

(i) Statute/Law/Policy/Regulations if any:

The Central Ground Water Authority has been constituted to regulate, control, development and management of ground water resources for whole country based on overall situation prevailing in India. But, the ground water conditions are varying from State to State. **Ground Water is a State subject and the State Government has every right to protect and regulate their own precious ground water resources according to the prevailing conditions in the State.**

The Tamil Nadu Government had enacted **“The Tamil Nadu Ground Water (Development and Management) Act, 2003”** which was subsequently **repealed in 2013**, so as to bring out an effective management Act considering the present scenario. **As an interim measure, for regulating the exploitation of ground water, the Government have issued G.O. (Ms) No.142,PWD dated 23.07.2014 for regulations for management of ground water for safe guarding the scarce groundwater resources in Tamil Nadu State.** In the absence of an Act, the Government executes this Government order to control, regulate and manage the Ground Water Resources while taking into consideration of the future of the State and its people.

The State Ground and Surface Water Resources Data Centre has estimated the Ground Water resources of Tamil Nadu State periodically in co-ordination with the Central Ground Water Board, Government of India, SECR, Chennai, based on the Methodology evolved by Ground Water Resources Estimation Committee, 1997 (GEC 97).

Accordingly, **the Ground Water Potential Assessment done as on January 1992 and as on January 1997 on the basis of Panchayat Union Blocks as assessment units** in Tamil Nadu and **categorized as Dark, Grey and White areas.** The Blocks with more than 85% to 100% ground water development were categorized as “Dark Blocks” and the blocks with ground water development between 65% to 85% were categorized as “Grey Blocks” and less than 65% ground water development were categorized as “White Blocks” and the Government approved the categorisation and released as Government order and G.O.No:326, PW (R2) Dept, dated: 23.11.1993. It was in effect up to the next assessment done as on March 2003.

Subsequently, **the Ground Water Potential Assessment done as on March 2003, categorized the blocks as Over Exploited, Critical, Semi Critical, Safe, Saline instead of Dark, Grey and White blocks.** The Blocks with more than 100% were categorized as “Over Exploited Blocks”, the blocks in between 90% to 100% as “Critical Blocks”, the blocks in between 65% to 90% as “Semi Critical Blocks” and less than 65% as “Safe Blocks” and the bad quality blocks were categorized as “Saline Blocks” and the same was approved by the Government

and released as G.O.No:51, PW (R2) Dept, dated: 11.02.2004. It was in effect up to the next assessment done as on March 2009.

The Next **Ground Water Potential Assessment done as on March 2009**, and the same was approved by the Government and released as **G.O.No:52,PW(R2) Dept, dated: 02.03.2012**.

As per G.O.No.52,PW(R2) Dept, dated: 02.03.2012 and G.O. (Ms) No.142,PW(R2)Dept dated 23.07.2014, the State Government have authorized and empowered the Chief Engineer, State Ground and Surface Water Resources Data Centre, Chennai for issuing permission or license or No Objection Certificate/renewal for drawal and transportation of Ground Water based on the hydro geological conditions to the New Industries, Packaged Drinking Water Companies, Infrastructures and Mining projects, etc except the areas to which the Chennai Metropolitan Area Ground Water (Regulation) Act,1987 extends.

Subsequently, the next **Ground Water Resources Assessment of the State was completed as on March 2011** and taking **Firka as an assessment unit** in the State of Tamil Nadu. Based on the above assessment, **the Government had approved and issued G.O.(Ms).No.113, Public Works (R2) Dept , Dt:09.06.2016** for categorisation of the Firkas in the State as Over Exploited, Critical, Semi-Critical and Safe Firkas. All the Over Exploited and Critical Firkas are notified as **“A” Category** (where the stage of ground water extraction is 90% and Above) and all the Semi Critical and Safe Firkas are notified as **“B” Category** (where the stage of ground water extraction is below 89%). In this Government Order, the Government had directed that **no Schemes should be formulated in the “A” Category Firkas and in “B” Category Firkas, all the Schemes should be formulated through State Ground and Surface Water Resources Data Centre by issuing No Objection Certificate for Ground Water Clearance.**

The term “Schemes” excludes Energisation of Agricultural pump sets by the Tamil Nadu Electricity Board. The present order may also exclude the Ground Water drawal for a). Domestic purpose by individual household, b). Domestic Infrastructure project (Housing), c).Government’s Drinking Water Supply Schemes and d). non water based industries, (i.e.- the industries which do not require and use

water, either as raw material or for other processing). However, the domestic use of water by this non water based industries will be permitted by the Chief Engineer / State Ground and Surface Water Resources Data Centre based on hydro geological conditions. (i.e. NOC from Chief Engineer, State Ground and Surface Water Resources Data Centre, Water Resources Department, Chennai). The list of non water based industries will be issued by the Industries Department of Government of Tamil Nadu separately.

Appropriate rain water harvesting and Artificial recharge schemes should be carried out in the categories viz , Over exploited , Critical , Semi Critical and Safe blocks of Tamil Nadu. While carrying out the above schemes, priority should be given to marginal quality and bad quality areas so as to avoid further deterioration.

All the schemes and proposals based on Ground Water will have to adhere to the Government orders and conditions. The Chief Engineer, State Ground and Surface Water Resources Data Centre had received the Government approval on Groundwater Assessment as on March 2011.

Regarding granting permission/ License for transportation of ground water for water suppliers/ private water tankers for selling the water on commercial basis, the State Ground and Surface Water Resources Data Centre, Public Works Department is not issuing any No Objection Certificate.

The Chief Engineer, SG&SWRDC have empowered to issue the NOC for drawal of Ground Water is up to 1 Million Gallons per day. Beyond this, the firms should get an approval in Water Utilisation Committee for drawal of both Surface and Ground Water resources in Tamil Nadu.

(ii) Suggestions for improvement of groundwater governance.

Groundwater is recognized as a common pool resource. The use of groundwater by anybody should in no way cause adverse impacts on realization of other person's fundamental right to safe water for life. Access to groundwater without any discrimination, equitable distribution, and sustainable use considering the needs of future generations are considered. Right to water

for life is the first priority and then to agriculture, and eco system needs. The precautionary principle and the polluter pay principle only to conserve and recharge groundwater.

The responsibility of the State for ensuring every person's right to safe water even when water service is delegated to a private agency. Groundwater is not amenable to ownership by the State, communities or persons and the State is the public trustee of groundwater. It also deals elaborately on groundwater protection and groundwater security plans.

The Groundwater Act should incorporate legal pronouncement on groundwater such as the public, trust doctrine and recognition of the right to groundwater. It addresses the deficiencies in the present legal frame work in dealing with over exploitation and includes the improvements to the control mechanism to ensure the qualitative and quantitative sustainability of groundwater resources. It proposes to strengthen the regulating powers of Panchayat and Municipal bodies related to Ground water in line with articles 243G and 243W of the constitution.

The Pricing of Ground Water for irrigation, Industrial and domestic purposes and collecting fees by water users association should be left to the State decision.

(iii) Institutions governing/managing/monitoring the resources and Institutional structure, gaps if any :

While framing the Groundwater Act, the recommendation for the constitution of (1) Gram Panchayat Groundwater Sub-Committee, (2) Block Panchayat Groundwater Management, (3) Ward Groundwater Committee, (4) Municipal Water Management Committee, (5) District Ground Water Council and (6) State Ground Water Advisory Council to control and manage Ground water should be considered.

- The constitution of aforesaid committees is completely based on administrative boundaries such as village, block, ward, municipality, district etc. But, with respect to water resources control and management issues and conflicts, the boundary should be based on river basins to have efficient monitoring and management of water resources. The Government of India, in all issues related

to water resources considered only the basin boundary concept. Hence, the institutional frame work has to be revised so as to have the jurisdiction of the committees with respect to basin / watershed concept. Further, Government of India, MoWR, RD &GR advocates time and again integrated water resources management. The above institutional frame work separately for groundwater is not in line with that.

- Further, it has also provided for many committees, viz., Gram Panchayat Groundwater Sub-Committee, Village Water and Sanitation Committee, Ward Committee, Municipal Committee, Block level Committee, District level Committee and State level Committee. For managing surface water resource water users association already exists. Too many committees at village / ward level would jeopardize the very purpose of managing the Groundwater resources efficiently and may invite lot of conflicts.

(iv) Areas of people/private participation if any:

The participation of people or private parties in the groundwater management is not suggestible, acceptable one and more chances of making litigations in the society and has unnecessary law and order problems may arise.

7. Tools and Methods

(i) Water Level and quality measurements through wells, piezometers, DWLR with telemetry, ground water elevation.

In general, water levels in the observation wells and piezometers can be taken manually by measuring tape. This is the simple, cost effective, good accuracy and less maintenance method. Water Levels are observed above the Measuring point.

Monitoring water level in DWLR with telemetry is costly, high maintenance, good accuracy, get the data immediately on desktop, easy to analysis purpose.

The water quality generally is analysed in the Chemical Lab only by collecting water samples in Pre Monsoon and post Monsoon period in the field. Sometimes, instant kits are used for analyzing the TDS and Ph level in the water.

(ii) Metering water supply to confirm contribution from groundwater.

Metering the water supply is essential one to monitor the overall usage of groundwater by different sectors. Flow meter must be fixed in every extraction structure and it has to be monitored periodically by Government officials.

8. Performance Indicators:

(i) Bench Marks/ Norms/ Standards and deviation from the norms/bench marks/ standards currently.

The Ground Water resources of State periodically estimated in co-ordination with the Central Ground Water Board, Government of India, SECR, Chennai, based on the Norms evolved by Ground Water Resources Estimation Committee, 1997 (GEC 97).

The ground water potential assessment can be assessed based on the bench marks such as Average Rainfall, Total recharged Area, Monthly Water Level Data, Total no of wells in the area, Irrigation methods adopted, Cropping pattern details, Geological conditions prevailing in that area, Specific yield, Seepage factor, Constructed Artificial recharge structures, etc and various calculations methods, etc, have to be considered.

Status of various Performance Indicators

(ii) Percentage of over exploited ,critical, Semi critical , Safe and Saline/Poor quality Firkas/area units

- Trend of over exploited and critical Firkas to total Firkas as per pervious assessment. (2009 Assessment Vs 2011 Assessment)

The Ground Water Potential Assessment as on March 2009, Out of 8 blocks in Dharmapuri District, 7 blocks are categorized as Over Exploited and Critical blocks and remaining 1 blocks are categorized as Semi Critical and Safe blocks.

The next Ground Water Resources Assessment of the State was done as on March 2011 and taking Firka as an assessment unit. In Dharmapuri District, totally 22 Firkas, 16 Firkas are categorized as Over Exploited and critical and remaining 8 Firkas are categorized as Semi Critical and Safe blocks.

Instead of taking Block as an assessment, Firka can be taken as assessment unit is to concentrate the assessment in micro level. For Eg, a block contains more than three to four Firkas. In this block, two Firkas may

have good groundwater potential than other two Firkas but it may to categorize as Over Exploited. To avoid this, assessment done on the basis of Firkas for the benefit of farmers to the implementation of schemes related to Irrigation.

The percentage of over exploited and critical Firkas has been increased by changing the concept from Block to Firka assessment. The total percentage of over exploited and critical Blocks for 2009 Assessment is 87.5%, but, the total percentage of over exploited and critical Firkas as on March 2011 Assessment is 72.72%, in the Dharmapuri District.

- Trend of over exploited and critical Firkas to total Firkas as per latest assessment

The percentage of over exploited and critical Firkas has been decreased in 2013 latest assessment when compared to 2011 assessment. In 2011 assessment, out of 22 Firkas, the total percentage of over exploited and critical Firkas is 72.72%, but, In 2013 assessment, out of 22 Firkas, it has been come down marginally to 81.81%, in the Dharmapuri District.

- Existing state of groundwater resources as compared to previous assessment (2013 Vs 2011 assessment).

Based on the Estimation of Ground Water Resources of Tamil Nadu State as on March 2013, Out of 22 Firkas in the District, 14 Firkas are categorized as “Over Exploited Firkas”, 4 Firkas are categorized as “Critical Firkas”, 3 Firkas are categorized as “Semi Critical Firkas”, 5 Firkas are categorized as “Safe Firkas”.

Based on the Estimation of Ground Water Resources of Tamil Nadu State as on March 2011, Out of 22 Firkas in the District, 14 Firkas are categorized as “Over Exploited Firkas”, 2 Firkas are categorized as “Critical Firkas”, Nil Firkas are categorized as “Semi Critical Firkas”, 8 Firkas are categorized as “Safe Firkas”.

When compared to last assessment as on March 2011, the “Over Exploited Firkas” maintains the same as 14 Firkas, the “Critical Firkas” increased from 2 to 4 Firkas, the “Semi Critical Firkas” increased marginally from Nil to 3 Firkas, the “Safe Firkas” increased from 8 to 5 and the “Saline Firkas” remains Nil Firkas. The alteration of Firkas are due to the construction

of Artificial Recharge structures such as Check Dams, Recharge Wells, Recharge shafts, percolation ponds; etc was constructed in the “Over Exploited Firkas” by various departments.

S.No	Categorisation	No of Firkas	
		2011	2013
1	Over Exploited	14	14
2	Critical	2	4
3	Semi Critical	Nil	3
4	Safe	8	5
5	Saline	Nil	Nil
TOTAL		22	22

(iii) Water Level(Well hydrographs and water level trends – pre and post monsoon such as declining trend/rising trend,etc).

(iv) Comparison of area irrigated from groundwater resources (Current assessment 2013 to previous assessment 2011).

S.No	Description	2011 Assessment	2013 Assessment
1	Area Irrigated from ground water resources(In hm)	6538.07	6505.06

(v) No. of groundwater abstraction structures (existing no. over the year and trends).

S.No	Description	2011 Assessment	2013 Assessment
1	No of groundwater abstraction structures for Irrigation	1,71,071 Wells	1,70,983 Wells

(vi) Trend in water quality (no of habitations affected with groundwater contamination like As, F, Salinity etc. Change in contamination level over the years.

(vii) Source augmentation (Groundwater)

- Area covered with infrastructure for recharging groundwater:

The proper artificial recharge structures has to be constructed based on local geological conditions in the areas of existing infrastructure for recharging groundwater according to their extraction needs.

- GW recharge plan to combat adversaries:

Groundwater recharge plans has to be strictly followed by with of implementing the groundwater laws to combat adversaries.

9. Reforms undertaken/being undertaken/proposed if any.

10. Road Map of activities/tasks proposed for better governance with timelines and agencies responsible for each task/activity.