

**CHAPTER 4.1.9 GROUND WATER RESOURCES
ERODE DISTRICT**

INDEX

CHAPTER	PAGE NO.
INTRODUCTION	3
ERODE DISTRICT – ADMINISTRATIVE SETUP	3
1. HYDROGEOLOGY	3-7
2. GROUND WATER REGIME MONITORING	8-15
3. DYNAMIC GROUND WATER RESOURCES	15-24
4. GROUND WATER QUALITY ISSUES	24-25
5. GROUND WATER ISSUES AND CHALLENGES	25-26
6. GROUND WATER MANAGEMENT AND REGULATION	26-32
7. TOOLS AND METHODS	32-33
8. PERFORMANCE INDICATORS	33-36
9. REFORMS UNDERTAKEN/ BEING UNDERTAKEN / PROPOSED IF ANY	
10. ROAD MAPS OF ACTIVITIES/TASKS PROPOSED FOR BETTER GOVERNANCE WITH TIMELINES AND AGENCIES RESPONSIBLE FOR EACH ACTIVITY	

GROUND WATER REPORT OF ERODE DISTRICT

INTRODUCTION :

In Tamil Nadu, the surface water resources are fully utilized by various stake holders. The demand of water is increasing day by day. So, groundwater resources play a vital role for additional demand by farmers and Industries and domestic usage leads to rapid development of groundwater. About 63% of available groundwater resources are now being used. However, the development is not uniform all over the State, and in certain districts of Tamil Nadu, intensive groundwater development had led to declining water levels, increasing trend of Over Exploited and Critical Firkas, saline water intrusion, etc.

ADMINISTRATIVE SET UP

The geographical extent of Erode district is 8.16 lakh hectares. The district has well laid out roads and railway lines connecting all major towns within and outside the State. For administrative purpose, this district has been bifurcated into seven Taluks, twenty Blocks and 34 Firkas.

Erode District is totally bifurcated into 34 Firkas.

1. HYDROGEOLOGY

(i) Major Geological formations:

Geology

Generally the entire area of the district is traversed by metamorphosed Gneissic rocks of Archean age. The northern parts of the district i.e. Thalamalai Reserved Forest and Bargur Reserved forest of the district are occupied by Charnockite. Similarly in the southern part of the district, the Charnockite is noticed in Dharapuram and Vellakoil areas.

In the central part, the country rock is intruded by intrusive rock like dolerite. The pegmatite intrusions are also observed here and there in the northern part of the district. The important rock types encountered in this area are Granitic gneiss, mica gneiss, hornblende gneiss, charnockite and pink granite.

Drilling of bore holes:

The occurrence and movement of groundwater in hard rock formations are restricted to the porous zones of weathered formations and the open systems of fractures, fissures and joints. Generally, in hard rock regions, occurrence of weathered thickness is discontinuous both in space and depth. Hence recharge of groundwater in hard rock formations is influenced by the intensity and depth of weathering. The subsurface lithological condition and the aquifer characters can be ascertained by drilling exploratory boreholes and conducting pump tests.

The State Ground and Surface Water Resources Data Centre, during the course of investigation has drilled more than 155 boreholes spread over the entire district to find out the nature and behaviour of the subsurface material and their water holding and water yielding capability. There is considerable diversity in the nature of formalities even within the short distance.

In the reserved forest area & hilly areas like Thalavadi and Anthiyur, the weathering zone is limited to 20 to 25 m below ground level. In the remaining parts of the district, the weathering zone varies from 10 to 30 m below ground level.

Aquifer parameters:

a) Hard rock

The thickness of aquifer in this district is highly erratic and varies between 10m to 30 m below ground level. The intergranular porosity is essentially dependent upon the intensity and degree of weathering and fracture development in the bed rock. As discussed earlier, deep weathering has developed in gneissic formations and moderate weathering in Charnockite formations. The range of aquifer parameters in the hard rock regions is given below.

Parameters	Range
Well yield in LPM	0.165-8.531lpm
Transmissivity (T) m ² /day	0.299-39.64 m ² /day
Permeability (K) m/day	0.0512-19.639 m/day

(iii) Drilling:

The drilling types are different according to the formation of the terrain. In general, DTH rigs are used in Hard rock formations for drilling a borewell at a depth ranges from 30m to 200m, according to the extension of joints, fractures, lineaments, etc in an area. In Sedimentary formations, rotary rigs with different rotors used according to the Tube well's diameter. The Bentonite clay is used in rotary rigs to avoid the collapse of the Tube well. The sedimentary tube wells are drilled up to a depth of 30m to 300m depending on the area, yield, etc. In alluvial formations, the hand rotary used for drilling tube wells ranges from 10m to 15m. In river beds, infiltration tube wells used for extraction of groundwater.

In Hard rock, the well designing is simple. The upper top soil and highly weathered zone is cased with PVC pipe and the remaining weathered, Fissured, Jointed portion is left as it is. In Villupuram District, the weathered zone ranges from 1.0m to 12.0m. In Granitic gneiss area, the highly weathered portion will be more up to 15m but in charnockite area, the weathered zone will extend up to 8.0m to 10.m only. In Sedimentary area, the well construction depends on the occurrence of sand thickness in the referred area. The logger is also used in the construction to identify the area of good quality of water.

2. GROUNDWATER REGIME MONITORING:

(i) Notes on existing water level scenario:

The water level is being monitored by State Ground & Surface Water Resources Data Centre from 1971 onwards from a network of 1746 observation wells (shallow open wells) located all over the State. The water level readings are observed in the first week of every month by the field officers. In Erode District, 191 observation wells and 65 piezometers, totally 256 wells are monitoring on Monthly basis. The Central Ground Water Board also monitors the water level from 900 numbers of wells spread all over the State. They observe water level four times in a year. (i.e January, May, August and November). The collected water level data are uploaded in GWDES software and database is maintained regularly for analysing the water level trend with rainfall. From the Monitoring network of wells, the selected representative wells are taken for Resource Estimation computations.

In Erode District, during the pre monsoon, the water level generally in declining trend ranges from G.L. to 15m. The depth of well below GroundLevel 12.0m are become dry during hot season like May, June, July. In the post monsoon, the water level generally in upward trend due to rainfall and it may reach the Ground Level also. The water level trend maps for pre and post monsoons are included as Annexure- I & II.

(ii) Long term trend of water level:

The long term fluctuations of water levels range from G.L. to 14.0m in many parts of the Erode District. The analysis reveals that the water level has gone down in the north, west and central parts of the Erode District. The inference taken from the annual fluctuation is due to lack of rainfall which in turn affects the groundwater levels in phreatic aquifer. The seasonal fluctuation study reveals that due to necessity for development of ground water for different sectored needs and due to failure of monsoons, the water level has gone down. The hydrograph of observation wells water level trend from 2005 to 2017 enclosed as Annexure – III and water level trend from 2000 to 2017 of Piezometers enclosed as Annexure – IV for Erode District.

(iii) Existing network of Monitoring wells:

In Erode District, the existing network of monitoring wells is 256 wells, 191 wells are observation wells and 65 wells are piezometers. These wells are observed for every month water level.

Erode District: Observation Wells - Location and Co-ordinates

Well No	District	Tahsil / Taluk	Block / Mandal	Village	Latitude	Longitude
53259	Erode	Perundurai		Vijayamangalam	11°14'30"	77°30'30"
53263	Erode	Perundurai		Sirukalanji	11°09'45"	77°29'25"
53264	Erode	Perundurai		Sellappagounde npalayam	11°09'00"	77°32'45"
53265	Erode	Perundurai		Unjakattuvalasu	11°07'00"	77°35'45"
53266	Erode	Perundurai		Pidariyur	11°11'40"	77°35'40"
53266(A)	Erode	Perundurai	Chennimalai	Pidariyur	11°11'36"	77°35'37"
53267	Erode	Perundurai		Singanallur	11°22'30"	77°32'16"

53268	Erode	Perundurai		Tiruvachi	11°18'21"	77°36'17"
53269	Erode	Perundurai		Karukkampalayam	11°13'31"	77°27'08"
63001	Erode	Gobichettipalayam	Nambiyur	Emmampoondi	11°18'30"	77°19'00"
63003	Erode	Gobichettipalayam	Nambiyur	Kumbapanai	11°19'50"	77°24'50"
63004	Erode	Sathyamangalam	Bhavanisagar	Panaiyarpalli	11°23'55"	77°09'25"
63004A	Erode	Sathyamangalam	Bhavani sagar	Pungampalli	11°40'37"	77°18'01"
63005	Erode	Sathyamangalam	Bhavanisagar	Punjaipuliampattay	11°10'00"	77°21'05"
63006	Erode	Sathyamangalam	Bhavanisagar	Kandisalai	11°22'20"	77°12'25"
63007	Erode	Sathyamangalam	Sathyamangalam	Ukkaram	11°24'30"	77°14'10"
63008	Erode	Gobichettipalayam	Nambiyur	Ariyanur	11°20'35"	77°16'00"
63009	Erode	Gobichettipalayam	Nambiyur	Sanarpudur	11°24'10"	77°17'30"
63010	Erode	Gobichettipalayam	Nambiyur	Nambiyur	11°21'35"	77°19'20"
63010A	Erode	Gobichettipalayam	Nambiyur	Nambiyur	11°21'29"	77°19'14"
63011	Erode	Gobichettipalayam	Nambiyur	Munampalli	11°24'05"	77°20'20"
63012	Erode	Gobichettipalayam	Nambiyur	Thithampalayam	11°21'40"	77°22'50"
63013	Erode	Gobichettipalayam	Nambiyur	Ayalur	11°24'15"	77°23'35"
63014	Erode	Gobichettipalayam	Gobichettipalayam	Kummikanikku	11°23'40"	77°26'10"
63015	Erode	Gobichettipalayam	Gobichettipalayam	Siruvalur	11°21'35"	77°27'40"
63015 A	Erode	Gobichettipalayam		Siruvalur	11°22'16"	77°27'41"
63016	Erode	Gobichettipalayam	Gobichettipalayam	Chellamadevi Pudur	11°23'10"	77°29'20"
63017	Erode	Sathyamangalam	Bhavanisagar	Muddukandurai	11°28'40"	77°08'45"
63018	Erode	Sathyamangalam	Bhavanisagar	Baguthampalayam	11°24'20"	77°10'45"
63018A	Erode	Sathyamangalam		Baguthampalayam	11°29'17"	77°10'08"
63019	Erode	Sathyamangalam	Bhavanisagar	Vinnapalli	11°25'05"	77°11'35"

63020	Erode	Sathyamangalam	Sathyamangalam	Shenbagapudur	11°27'35"	77°13'00"
63021	Erode	Sathyamangalam	Sathyamangalam	Indiampalayam	11°26'50"	77°16'20"
63022	Erode	Gobichettipalayam	T.N.Palayam	Perikoduveri	11°28'40"	77°18'10"
63023	Erode	Gobichettipalayam	Gobichettipalayam	Alukuli	11°26'45"	77°21'30"
63024	Erode	Gobichettipalayam	Gobichettipalayam	Gobichettipalayam	11°27'10"	77°26'20"
63025	Erode	Gobichettipalayam	Gobichettipalayam	Sanarpalayam	11°26'55"	77°24'40"
63026	Erode	Gobichettipalayam	Gobichettipalayam	P.Mettupalayam	11°27'00"	77°34'20"
63027	Erode	Sathyamangalam	Sathyamangalam	Pudukuyanoor	11°32'30"	77°09'20"
63028	Erode	Sathyamangalam	Sathyamangalam	Chikkarasampalayam	11°32'00"	77°13'30"
63029	Erode	Sathyamangalam	Sathyamangalam	Sathyamangalam	11°30'30"	77°14'40"
63030	Erode	Sathyamangalam	T.N.Palayam	Kembanaickenpalayam	11°30'40"	77°18'00"
63031	Erode	Gobichettipalayam	T.N.Palayam	Vaniputhur	11°30'20"	77°21'50"
63031 A	Erode	Gobichettipalayam		Vaniputhur	11°30'26"	77°21'45"
63032	Erode	Gobichettipalayam	T.N.Palayam	Bungalowpudur	11°30'25"	77°24'40"
63033	Erode	Gobichettipalayam	T.N.Palayam	Kallipatty	11°30'50"	77°27'20"
63033 A	Erode	Gobichettipalayam		Kallipatty	11°30'59"	77°27'08"
63034	Erode	Gobichettipalayam	Gobichettipalayam	Sanandapur	11°31'10"	77°30'30"
63037	Erode	Sathyamangalam	Thalavadi	Byyanapuram	11°42'00"	77°53'40"
63038	Erode	Sathyamangalam	Thalavadi	Tignarai	11°42'50"	77°58'00"
63039	Erode	Sathyamangalam	Thalavadi	Chikkahally	11°44'10"	77°02'30"
63040	Erode	Sathyamangalam	Thalavadi	Hasanur	11°40'0 "	77°08'20"
63040A	Erode	Sathyamangalam	Thalavadi	Hasanur	11°01'07"	77°13'11"
63041	Erode	Sathyamangalam	Thalavadi	Mallankuli	11°45'10"	77°55'20"

63042	Erode	Sathyamangalam	Thalavadi	Thalavadi	11°46'50"	77°01'20"
63042 A	Erode	Sathyamangalam	Thalavadi	Kumtapuram	11°46'43"	77°01'23"
63043	Erode	Sathyamangalam	Sathyamangalam	Arasur	11°05'10"	77°06'58"
63044	Erode	Gobichettipalayam		Kosanam	11°22'51"	77°19'51"
63045	Erode	Gobichettipalayam		E.chettipalayam	11°18'16"	77°43'30"
63101	Erode	Bhavani	Bhavani	Chettipalayam	11°24'30"	77°35'30"
63102	Erode	Bhavani	Bhavani	Odathurai	11°27'20"	77°30'50"
63103	Erode	Bhavani	Andhiyur	Nallagoundanpudur	11°29'35"	77°33'25"
63104	Erode	Bhavani	Bhavani	Kaundapadi	11°25'20"	77°33'50"
63105	Erode	Bhavani	Bhavani	Jambai	11°28'05"	77°38'20"
63106	Erode	Bhavani	Bhavani	Poolapalayam	11°25'40"	77°38'30"
63107	Erode	Bhavani	Bhavani	Thottypalayam	11°28'30"	77°40'10"
63108	Erode	Bhavani	Bhavani	Bhavani	11°26'50"	77°41'05"
63109	Erode	Bhavani	Andhiyur	Athani	11°31'20"	77°30'30"
63110	Erode	Bhavani	Andhiyur	Thoppur Paraiyur	11°32'05"	77°32'50"
63111	Erode	Bhavani	Andhiyur	Brammadesam	11°32'30"	77°35'50"
63112	Erode	Bhavani	Andhiyur	Andiyur	11°34'05"	77°35'05"
63113	Erode	Bhavani	Andhiyur	Sembulichampalayam	11°32'45"	77°36'50"
63114	Erode	Bhavani	Andhiyur	Naal Road	11°32'45"	77°36'50"
63114A	Erode	Bhavani		Naal Road Sokkanathamalai	11°20'51"	77°39'46"
63115	Erode	Bhavani	Bhavani	Thurusanpalayam	11°30'35"	77°38'20"
63116	Erode	Bhavani	Bhavani	Kondireddipalayam	11°32'05"	77°46'10"
63117	Erode	Bhavani	Bhavani	Kammagoundanpudur	11°30'50"	77°42'05"
63118	Erode	Bhavani	Ammamet	Kesari Mangalam	11°32'20"	77°43'30"
63119	Erode	Bhavani	Andhiyur	Pudupalayam	11°35'35"	77°35'10"
63120	Erode	Bhavani	Andhiyur	Chellampalayam	11°37'55"	77°35'05"
63121	Erode	Bhavani	Ammamet	Vellithirupur	11°37'10"	77°38'05"
63121A	Erode	Bhavani	Anthiyur	Vellithiruppur	11°37'06"	77°37'54"
63122	Erode	Bhavani	Ammamet	Reddipalayam	11°38'05"	77°39'15"
63122 A	Erode	Bhavani		Reddipalayam-chipanthikat	11°07'07"	79°10'18"

63123	Erode	Bhavani	Ammamet	Attavanaipudur	11°35'15"	77°39'45"
63124	Erode	Bhavani	Ammamet	Unjapalayam	11°36'20"	77°42'05"
63125	Erode	Bhavani	Ammamet	Surigampet	11°35'30"	77°43'55"
63126	Erode	Bhavani	Ammamet	Ammamet	11°37'10"	77°44'40"
63127	Erode	Bhavani	Ammamet	Nerinjipet	11°34'10"	77°45'30"
63128	Erode	Bhavani	Ammamet	Chennampatti	11°40'45"	77°40'45"
63129	Erode	Bhavani		Periyavadamola palayam	11°29'10"	77°37'10"
63130	Erode	Bhavani		Varadanallur	11°29'34"	77°42'33"
63131	Erode	Bhavani		Komarayanur	11°44'20"	77°41'33"
63132	Erode	Bhavani		Vempatty	11°31'25"	77°34'50"
63132A	Erode	Bhavani	Anthiyur	Nallamooanur	11°30'47"	77°35'15"
63133	Erode	Bhavani		Ennamangalam	11°38'40"	77°35'40"
63134	Erode	Bhavani		Sanathikalmedu	-	-
63135	Erode	Bhavani		Maathur	11°37'18"	77°37'04"
63202	Erode	Erode	Kodumudi	Perymalkoilpu du r	11°04'40"	77°50'44"
63203	Erode	Erode	Kodumudi	Kodumudi	11°04'35"	77°53'05"
63214	Erode	Erode	Kodumudi	Thoppapalayam	11°08'25"	77°48'40"
63215	Erode	Erode	Modakurichi	Palamangalam	11°09'45"	77°48'55"
63216	Erode	Erode	Modakurichi	Unjalur	11°07'40"	77°52'40"
63223	Erode	Perundurai	Chennimalai	Irugur	11°14'20"	77°35'00"
63224	Erode	Perundurai	Chennimalai	Maladi	11°11'30"	77°37'25"
63225	Erode	Perundurai	Chennimalai	Vadamuga Vello du	11°14'18"	77°38'12"
63225 A	Erode	Perundurai	Chennimalai	Vello du	11°14'17"	77°39'53"
63226	Erode	Erode	Modakurichi	Avalpundurai	11°13'38"	77°43'05"
63226 A	Erode	Erode	Modakurichi	Avalpoondurai	11°14'07"	77°43'10"
63227	Erode	Erode	Modakurichi	Elamathur	11°11'40"	77°46'45"
63228	Erode	Erode	Modakurichi	Modakurichi	11°13'55"	77°46'40"
63229	Erode	Erode	Kodumudi	Solengapalaya m	11°14'40"	77°50'45"
63230	Erode	Erode	Kodumudi	Punjaikolanalli	11°10'38"	77°51'05"
63231	Erode	Perundurai	Perundurai	Kunnathur	11°06'25"	77°24'45"
63232	Erode	Perundurai	Perundurai	Pallpavalasu	11°16'45"	77°27'00"
63232A	Erode	Perundurai	Perundurai	Pappavalasu	11°16'44"	77°17'27"
63233	Erode	Perundurai	Perundurai	Natha Kattu Palayam	11°19'35"	77°29'30"
63234	Erode	Perundurai	Perundurai	Karandipalayam	11°16'50"	77°29'44"
63235	Erode	Perundurai	Perundurai	Kullampalayam	11°16'25"	77°31'45"
63235 A	Erode	Perundurai	Perundurai	Kallakulam	11°16'35"	77°31'13"
63236	Erode	Perundurai	Perundurai	Perundurai	11°16'35"	77°35'00"
63236 A	Erode	Perundurai	Perundurai	Perundurai	11°16'35"	77°35'05"

63237	Erode	Erode	Erode	Veppampalaya m	11°17'49"	77°38'35"
63238	Erode	Erode	Erode	Sengodampalaya am	11°19'40"	77°40'50"
63239	Erode	Erode	Erode	Senapattipalaya m	11°17'22"	77°41'45"
63240	Erode	Erode	Erode	Nathagoundamp alayam	11°16'10"	77°43'23"
63240 A	Erode	Erode	Modakurichi	Kaspapettai	11°16'38"	77°43'38"
63241	Erode	Erode	Erode	Kollampalayam	11°19'15"	77°43'25"
63242	Erode	Erode	Erode	Pudur Lakkapuram	11°17'35"	77°44'52"
63243	Erode	Perundurai	Perundurai	Nallampatty	11°20'30"	77°32'18"
63244	Erode	Perundurai	Perundurai	Kanjikoil	11°22'08"	77°38'50"
63245	Erode	Erode	Erode	Nasiyanur	11°20'08"	77°38'30"
63246	Erode	Erode	Erode	Chithodu	11°23'45"	77°39'35"
63247	Erode	Erode	Erode	Agraharam	11°22'10"	77°43'35"
63247 (A)	Erode	Erode	Erode	Veerappappnnc hathiram	11°21'06"	77°42'44"
63248	Erode	Erode		Perumalpalaya m	11°33'34"	77°32'21"
63249	Erode	Erode		Arachalur	11°09'50"	77°42'15"
63250	Erode	Erode		Vilakethi	11°08'06"	77°45'57"
63251	Erode	Erode		Ichipalayam	11°04'20"	77°50'25"
63252	Erode	Erode		Thamaraipalaya m	11°06'35"	77°51'25"
63253	Erode	Erode		Attavanai Anumanpalli	11°10'54"	77°40'24"
63254	Erode	Erode		Kagam	11°08'33"	77°46'25"
63255	Erode	Erode		Kangayampalaya am	11°01'28"	77°09'04"
63256	Erode	Erode		Sengodampalaya am	11°19'34"	77°41'03"
63257	Erode	Erode		Samynathapura m	11°09'21"	77°43'19"
63266 A	Erode	Perundurai	Chennimalai	Pidariyur	11°11'36"	77°35'37"
63501	Erode	Dharapuram	Dharapuram	Mundavelampatt y	10°42'30"	77°19'40"
63502	Erode	Dharapuram	Dharapuram	Dasarapatty	10°40'50"	77°21'35"
63503	Erode	Dharapuram	Dharapuram	Ponnapuram	10°04'40"	77°23'30"
63504	Erode	Dharapuram	Dharapuram	Reddipalayam	10°43'10"	77°27'30"
63505	Erode	Dharapuram	Dharapuram	Dalavaypattina m	10°40'25"	77°29'00"
63506	Erode	Dharapuram	Dharapuram	Dharapuram	10°45'55"	77°31'30"
63507	Erode	Dharapuram	Dharapuram	Manakkadavu	10°40'20"	77°32'35"
63508	Erode	Dharapuram	Dharapuram	Koneripatti	10°42'15"	77°36'00"

63509	Erode	Dharapuram	Mulanur	Ponnivadi	10°41'55"	77°38'45"
63510	Erode	Dharapuram	Kundadam	P.K.Palayam	10°46'15"	77°18'50"
63511	Erode	Dharapuram	Dharapuram	Marudur	10°45'50"	77°22'35"
63512	Erode	Dharapuram	Kundadam	Sadayapalayam	10°48'15"	77°22'40"
63513	Erode	Dharapuram	Dharapuram	Rangampalayam	10°46'25"	77°27'20"
63514	Erode	Dharapuram	Kundadam	Suriyanallur	10°49'05"	77°28'35"
63515	Erode	Dharapuram	Dharapuram	Varapalayam	10°46'40"	77°30'40"
63516	Erode	Dharapuram	Dharapuram	Pallapalayam	10°47'50"	77°32'40"
63517	Erode	Dharapuram	Dharapuram	Kulathupalayam	10°45'35"	77°35'00"
63518	Erode	Dharapuram	Mulanur	S.K.Palayam	10°49'40"	77°35'10"
63519	Erode	Dharapuram	Dharapuram	Peranium	10°48'40"	77°37'45"
63520	Erode	Dharapuram	Dharapuram	Polarai	10°45'55"	77°40'05"
63521	Erode	Dharapuram	Mulanur	Nattapalayam	10°49'40"	77°40'40"
63522	Erode	Dharapuram	Mulanur	Mulanur	10°47'40"	77°42'25"
63523	Erode	Dharapuram	Mulanur	Kilankundal	10°45'05"	77°43'35"
63524	Erode	Dharapuram	Mulanur	Unnukarai	11°45'25"	77°46'55"
63525	Erode	Dharapuram	Mulanur	Kannivadi	10°48'40"	77°47'00"
63526	Erode	Dharapuram	Mulanur	Nanjaikalipalayam	10°50'00"	77°50'00"
63527	Erode	Dharapuram	Mulanur	Malamedu	10°47'25"	77°52'15"
63528	Erode	Dharapuram	Kundadam	Karilingampalayam	10°50'30"	77°18'20"
63529	Erode	Dharapuram	Kundadam	N.V.Palayam	10°50'40"	77°21'45"
63530	Erode	Dharapuram	Kundadam	Kundadam	10°50'45"	77°26'45"
63531	Erode	Dharapuram	Kundadam	Dayampalayam	10°53'00"	77°39'35"
63532	Erode	Dharapuram	Kundadam	Uthiyur	10°53'40"	77°31'40"
63533	Erode	Dharapuram	Kundadam	Sinukinaru	10°50'20"	77°33'05"
63534	Erode	Dharapuram	Kundadam	Anaipudur	10°52'30"	77°35'55"
63535	Erode	Kangayam	Vellakoil	Andipalayam	10°52'00"	77°39'00"
63536	Erode	Kangayam	Vellakoil	Erichinampalayam	10°50'40"	77°44'30"
63537	Erode	Kangayam	Vellakoil	Muthunaickken Valasu	10°54'10"	77°44'35"
63538	Erode	Kangayam	Vellakoil	Punjathalaiyur	10°51'20"	77°48'30"
63539	Erode	Dharapuram	Mulanur	Nathamvalasu	10°55'05"	77°27'10"
63540	Erode	Kangayam	Kangayam	Kadaiyur	10°59'05"	77°36'30"
63541	Erode	Kangayam	Kangayam	Olapalayam	10°59'30"	77°33'50"
63542	Erode	Kangayam	Vellakoil	Vellakoil	10°56'40"	77°42'55"

Erode District: 111 - Piezometers - Location and Co-ordinates

Well no	District	Tashil/Taluk	Block/Mandal	Village	Latitude	Longitude
HP1E01	Erode	Bhavani	Ammamet	Boothapadi	11.6027 78	77.711111

HP1E02	Erode	Bhavani	Andhiyur	Andhiyur	11.5777 78	77.588889
HP1E03	Erode	Bhavani	Andhiyur	Pudupalayam	11.6208 33	77.587500
HP1E04	Erode	Bhavani	Andhiyur	Brammadesam	11.5458 33	77.579167
HP1E04 A	Erode	Bhavani	Andhiyur	Bramadesam	11.5458 33	77.579167
HP1E05	Erode	Gobichettipala yam	T.N.Palayam	Vaniputhur	11.5097 22	77.362500
HP1E05 A	Erode	Gobichettipala yam	T.n.palayam	Vaniputhur	11.51	77.361667
HP1E06	Erode	Bhavani	Bhavani	Thurusampalaya m	11.5111 11	77.636111
HP1E06 A	Erode	Bhavani	Bhavani	Thurusampalaya m	11.5111 11	77.637222
HP1E07	Erode	Perundurai	Perundurai	Perundurai	11.2763 89	77.584722
HP1E08	Erode	Erode	Modakurichi	Modakurichi	11.2319 44	77.779167
HP1E09	Erode	Erode	Kodumudi	Vengambur	11.1041 67	77.879167
HP1E12	Erode	Perundurai	Perundurai	Kullampalayam	11.2722 22	77.530556
HP1E12 A	Erode	Perundurai	Perundurai	Kullampalayam	11.2722 22	77.530556
HP1E14	Erode	Gobichettipala yam	Nambiyur	Nambiyur	11.3694 44	77.323611
HP1E14A	Erode	Gobichettipala yam	Nambiyur	Nambiyur	11.3569 44	77.317500
HP1E15	Erode	Gobichettipala yam	Gobichettipalaya m	Ayalur	11.4097 22	77.408333
HP1E16	Erode	Sathyamangal am	Sathyamangalam	Rajannagar	11.5416 67	77.154167
HP1E17	Erode	Sathyamangal am	Thalavadi	Hasanur	11.675	77.145833
HP1E18	Erode	Sathyamangal am	Thalavadi	Thalavadi	11.7722 22	77.005556
HP1E19	Erode	Gobichettipala yam	Gobichettipalaya m	Siruvalur	11.3625	77.462500
HP1E19 A	Erode	Gobichettipala yam	Gobichettipalaya m	Siruvalur	11.3625	77.462500
HP1E20	Erode	Bhavani	Andhiyur	Thoppur paraiyaur	11.5333 33	77.533333
HP1E20 A	Erode	Bhavani	Andhiyur	Thoppuparaiyur	11.5366 67	77.549444

HP2E01	Erode	Erode	Erode	Suriyampalayam	11.3958 33	77.691667
HP2E02	Erode	Erode	Erode	Senapathipalaya m	11.2916 67	77.695833
HP2E03	Erode	Erode	Kodumudi	Kandasamypalay am	11.1083 33	77.737500
HP2E04	Erode	Bhavani	Ammamet	Kesaripalayam	11.5305 56	77.705556
HP2E05	Erode	Bhavani	Bhavani	Jambai	11.4638 89	77.644444
HP2E06	Erode	Perundurai	Perundurai	Kanchikovil	11.4666 67	77.595833
HP2E07	Erode	Perundurai	Chennimalai	Vedamugamvello du	11.2527 78	77.662500
HP2E08	Erode	Perundurai	Chennimalai	Orathupalayam	11.1111 11	77.541667
HP2E14	Erode	Sathyamangal am	Bhavanisagar	Ayyampalayam	11.3916 67	77.083889
HP2E15	Erode	Sathyamangal am	Bhavanisagar	Panayampalli	11.3958 33	77.151389
HP2E16	Erode	Sathyamangal am	Sathyamangalam	Ukkaram	11.4097 22	77.234722
HP2E17	Erode	Gobichettipala yam	T.N.Palayam	Thadapalligrama m	11.4583 33	77.337500
HP2E18	Erode	Gobichettipala yam	Nambiyur	Kadathur	11.4138 89	77.279167
HP2E19	Erode	Gobichettipala yam	T.n.palayam	Kodayampalaya m	11.5125	77.436111
HP2E20	Erode	Gobichettipala yam	Nambiyur	Vemandampalay am	11.3216 67	77.262500
HP2E31	Erode	Erode	Modakurichi	T.mettupalayam	11.2597 22	77.705556
HP2E32	Erode	Erode	Erode	Chithode	11.3925	77.660833
HP2E33	Erode	Bhavani	Bhavani	Punnam	11.5041 67	77.614722
HP2E34	Erode	Bhavani	Bhavani	Chettipalayam	11.4094 44	77.607500
HP2E35	Erode	Perundurai	Perundurai	Pulavarpalayam	11.3786 11	77.578889
HP2E36	Erode	Perundurai	Perundurai	Periyavilamalai	11.3386 11	77.607500
HP2E37	Erode	Erode	Erode	Gangapuram	11.3697 22	77.653611
HP2E38	Erode	Erode	Modakurichi	Injampalli	11.2222 22	77.826111

HP3E01	Erode	Erode	Erode	B.P.agraharam	11.3694 44	77.708333
IBH-61268	Erode	Bhavani	Andhiyur	Athani	11.5458 33	77.504167
IBH-61269	Erode	Bhavani	Andhiyur	Brammadesam	11.5472 22	77.613889
IBH-61271	Erode	Bhavani	Anthiyur	Pudupalayam	11.4813 89	77.580833
IBH-61273	Erode	Bhavani	Bhavani	Senthampalayam	11.4383 33	77.565000
IBH-61275	Erode	Bhavani	Bhavani	V.Mettupalayam	11.5038 89	77.711111
IBH-61278	Erode	Bhavani	Anthiyur	Moongilpatty	11.5075	77.536111
IBH-61294	Erode	Gobichettipala yam	Nambiyur	Nambiyur	11.3611 11	77.321667
IBH-61296	Erode	Gobichettipala yam	Gobichettipalaya m	Vellankoil	11.3822 22	77.482778
MWSE01	Erode	Sathyamangal am	Sathyamangalam	Kumarapalayam	11.5013 89	77.265278
MWSE02	Erode	Gobichettipala yam	T.n.palayam	Periakodiveri	11.4988 89	77.287222
MWSE03	Erode	Gobichettipala yam	Gobichettipalaya m	Kottupullampalay am	11.4416 67	77.384167
MWSE04	Erode	Gobichettipala yam	Gobichettipalaya m	P. Mettupalayam	11.4641 67	77.528333
MWSE05	Erode	Perundurai	Chennimalai	Koothampalayam	11.1541 67	77.506944
MWSE08	Erode	Erode	Kodumudi	Vallipuram	11.0891 67	77.810000
MWSE09	Erode	Erode	Modakurichi	Avalpoondurai	11.2269 44	77.737500
MWSE10	Erode	Erode	Erode	Elavamalai	11.4280 56	77.653333
MWSE11	Erode	Bhavani	Ammamet	Kurichi	11.5613 89	77.692778

(iv) Data Constraints:

The following are constraints in collecting the water level data in the field and validating the data are:

- 1) The water level data are collected on the monthly basis in the referred observation wells and piezometers. The collected data is not sufficient quantity for analyzing purpose due to drying of wells, Wells abounded by various reasons, lack of selecting the alternate wells, lack of open wells available for monitoring purpose due to increased usage of bore wells in the villages,

Panchayats, etc. In many villages, the water supply schemes implemented by overhead tank supply or mini energised pumps and the existing open wells are not used generally by the villagers and moreover, they filled with garbage.

- 2) The number of bore wells should be increased for monitoring purpose.
- 3) The site selection of new bore wells should be based on the Geological methods.
- 4) Strengthening the network of monitoring wells by closing the gaps in the network.
- 5) Maintenance cost should be allotted to maintain the bore wells on the periodical basis to maintain the quality as well as yield.
- 6) Installation of Automatic water level recorders in the sensitive and more water level fluctuation in the bore wells will helpful to monitor the extensive depletion of groundwater areas.
- 7) Upgrading the measuring instruments will helpful to take accurate reading of water levels in the field.
- 8) Upgrading the soft ware will helpful to minimize the errors and increasing the accuracy of data.
- 9) Erecting the Telemetric water level recorders in the over exploited Firkas will helpful to monitor the over extraction of groundwater.
- 10) Lack of manpower and transporting vehicles are also major problems for data collection in the field in proper time.

3. DYNAMIC GROUND WATER RESOURCES:

The State Ground and Surface Water Resources Data Centre has estimated the ground water resources of Tamil Nadu periodically in co-ordination with the Central Ground Water Board, Government of India , Ministry of Water Resources, Chennai, based on the Methodology evolved by the Ground Water Resources Estimation Committee, 1997 (GEC 97).

Groundwater potential assessment is a dynamic one and not static. While assessing an area, the following factors can be considered such as Geology, Total Irrigated Area, Total Number of Wells used for Irrigation, Water Level Data for the past five years, Average Rainfall, Total Recharge, Irrigation methods adopted in the area, Cropping pattern details, Seepage factor, Specific yield, Geological

conditions prevailing in that area, Recharge through Artificial recharge structures, etc.

Groundwater potential assessment proposal should be presented for approval in the Central and State Level Working Group Committees and then, presented for final approval in the Central Level Committee as well as State Level Committees.

The Ground Water Potential Assessments as on January 1992 and January 1997 were done in the State, taking the Panchayat Union Block as an Assessment Unit and the entire State **was categorized as Dark, Grey and White areas**. The Blocks with more than 85% to 100% ground water development (extraction) were categorized as “Dark Blocks” and the blocks with ground water development between 65% to 85% were categorized as “Grey Blocks” and blocks with less than 65% ground water development were categorized as “White Blocks”.

Subsequently, the **Ground Water Potential Assessment was done as on March 2003 and as on March 2009**. In these assessments, the Panchayat Union Blocks in Tamil Nadu were **categorized as Over-Exploited, Critical, Semi-Critical, Safe and Saline instead of Dark, Grey and White blocks**. The Blocks with more than 100% extraction were categorized as “Over Exploited Blocks”, the blocks with 90% to 100% extraction as “Critical Blocks”, the blocks with 65% to 90% extraction as “Semi Critical Blocks”, the blocks with less than 65% extraction as “Safe Blocks” and the bad quality blocks were categorized as “Saline Blocks”. No schemes should be formulated in over exploited and critical blocks - “Notified Blocks – A category – (Stage of Groundwater extraction is 90% and above)”.

The re-estimation of groundwater resources in the State as on March 2011 and as on March 2013 can be assessed in Micro Level basis. In these assessments, the assessing unit is Firka (Unit of Taluk) and **categorized as Over-Exploited, Critical, Semi-Critical, Safe, and Saline Firkas**. As on March 2013 assessment, in the Villupuram District

Based on the Estimation of Ground Water Resources of Tamil Nadu State as on March 2013, Out of 1139 Firkas in the State, 358 Firkas are

categorized as “Over Exploited Firkas”, 105 Firkas are categorized as “Critical Firkas”, 212 Firkas are categorized as “Semi Critical Firkas”, 429 Firkas are categorized as “Safe Firkas” and 35 Firkas are categorized as “Saline Firkas”.

When compared to last assessment as on March 2011, the “Over Exploited Firkas” comes down from 374 to 358 Firkas, the “Critical Firkas” increased from 48 to 105 Firkas, the “Semi Critical Firkas” comes down marginally from 235 to 212 Firkas, the “Safe Firkas” comes down marginally from 437 to 429 Firkas and the “Saline Firkas” remains same as 35 Firkas. The alteration of Firkas are due to the construction of Artificial Recharge structures such as Check Dams, Recharge Wells, Recharge shafts, percolation ponds; etc was constructed in the “Over Exploited Firkas” by various departments.

Methodology adopted for Estimation of Ground Water Potential :

The present methodology used for resources assessment is known as Ground Water Resource Estimation Methodology - 1997 (GEC'97) .In GEC'97, two approaches are recommended - **water level fluctuation method and norms of rainfall infiltration method**. The water level fluctuation method is based on the concept of storage change due to differences between various input and output components. Input refers to recharge from rainfall and other sources and subsurface inflow into the unit of assessment. Output refers to ground water draft, ground water evapotranspiration, base flow to streams and subsurface outflow from the unit. Since the data on subsurface inflow / outflow are not readily available, it is advantageous to adopt the unit for ground water assessment as basin / sub basin / watershed, as the inflow / outflow across these boundaries may be taken as negligible.

In each assessment unit, hilly areas having slope more than 20% are deleted from the total area to get the area suitable for recharge. Further, areas where the quality of ground water is beyond the usable limits should be identified and handled separately. The remaining area after deleting the hilly area and separating the area with poor ground water quality is to be delineated into command and non-command areas. Ground water assessment in command and non-command areas are done separately for monsoon and non-monsoon seasons.

The rainfall recharge during monsoon season computed by Water Level Fluctuation (WLF) method is compared with recharge figures from Rainfall Infiltration

Factor (RIF) method. In case the difference between the two sets of data are more than 20% then RIF figure is considered, otherwise monsoon recharge from WLF is adopted. While adopting the rainfall recharge figures, weight age is to be given to WLF method over adhoc norms method of RIF. Hence, wherever the difference between RIF & WLF is more than 20%, data have to be scrutinized and corrected accordingly.

During non-Monsoon season, rainfall recharge is computed by using Rainfall infiltration Factor (RIF) method. Recharge from other sources is then added to get total non-Monsoon recharge. In case of areas receiving less than 10% of the annual rainfall during non-monsoon season, the rainfall recharge is ignored.

The total annual ground water recharge of the area is the sum-total of monsoon and non-monsoon recharge. An allowance is kept for natural discharge in the non-monsoon season by deducting 5 to 10 % of total annual ground water recharge.

The balance ground water available accounts for existing ground water withdrawal for various uses and potential for future development. This quantity is termed as Net Ground Water Availability.

Net Ground Water Availability = Annual Ground Water Recharge - Natural discharge during non-monsoon season.

GEC'97 methodology has recommended norms for various parameters being used in ground water recharge estimation. These norms vary depending upon water bearing formations and agroclimatic conditions. While norms for specific yield and recharge from rainfall values are to be adopted within the guidelines of GEC'97, in case of other parameters like seepage from canals, return flow from irrigation, recharge from tanks & ponds, water conservation structures, results of specific case studies may replace the adhoc norms.

The Gross yearly ground water draft is to be calculated for Irrigation, Domestic and Industrial uses. The gross ground water draft would include the ground water extraction from all existing ground water structures during monsoon as well as during non-monsoon period. While the number of ground water structures should preferably be based on latest well census, the average unit draft from different types of structures should be based on specific studies or adhoc norms given in GEC'97 report.

The stage of Ground water Development is defined by

$$\text{Stage of Ground water Development (\%)} = \frac{\text{Existing Gross Ground water Draft for all uses}}{\text{Net annual Ground Water Availability}} \times 100$$

The units of assessment are categorized for ground water development based on two criteria – a) stage of ground water development and b) long-term trend of pre and post monsoon water levels. Four categories are - Safe areas which have ground water potential for development; Semi-critical areas where cautious ground water development is recommended; Critical areas; Over -exploited areas where there should be intensive monitoring and evaluation and future ground water development be linked with water conservation measures.

The criteria for categorization of assessment units are as follows:

S. No.	Stage of Groundwater Development	Significant Long term Decline		Categorization
		Pre-monsoon	Post -monsoon	
1.	<=70%	No	No	SAFE
		Yes / No	No / Yes	To be re-assessed
		Yes	Yes	To be re-assessed
2.	>70% and <=90%	No	No	To be re-assessed
		Yes / No	No / Yes	SEMI – CRITICAL
		Yes	Yes	SEMI – CRITICAL
3.	>90 and <=100%	No	No	To be re-assessed
		Yes / No	No / Yes	CRITICAL

		Yes	Yes	CRITICAL
4.	>100%	No	No	To be re-assessed
		Yes / No	No / Yes	OVER- EXPLOITED
		Yes	Yes	OVER- EXPLOITED

Note: 'To be re-assessed' means that data is to be checked and reviewed. If the ground water resources assessment and the trend of long term water levels contradict each other. This anomalous situations requires a review of the ground water resource computations, as well as the reliability of water level data.

The long term ground water level data should preferably be for a period of 10 years. The significant water level decline may be taken in consideration between 10 to 20 cm/ year depending upon the local hydro geological conditions.

Dynamic Ground Water Resources Estimation of TamilNadu As on March 2013

District Summary

(in ha.m)

ERODE DISTRICT							
Sl.No (District)	District	Net Annual Ground Water Availability	Existing Gross Ground Water Draft for Irrigation	Existing Gross Ground Water Draft for domestic and industrial water supply	Existing Gross Ground Water Draft for All uses (4+5)	Stage of Ground Water Development $\{(6/3)*100\}$ %	No of Over Exploited Firkas
1	2	3	4	5	6	7	8
1	ERODE	67,024.26	57,638.30	6,029.53	63,667.83	95	12

Firka Wise Summary
(in ha.m)

ERODE DISTRICT							
Sl.No	Assessment Unit (Firka)	Net Annual Ground Water Availability	Existing Gross Ground Water Draft for Irrigation	Existing Gross Ground Water Draft for domestic and industrial water supply	Existing Gross Ground Water Draft for All uses (4+5)	Stage of Ground Water Development $\{(6/3)*100\}$ %	Category of the Firka
1	AMMAPETTAI	2,151.34	1,869.15	99.56	1,968.71	92	CRITICAL
2	ANTHIYUR	1,808.32	1,742.88	95.52	1,838.40	102	OVER EXPLOITED
3	ARACHALUR	3,119.97	2,972.50	76.41	3,048.91	98	CRITICAL
4	ARASUR	1,790.51	1,503.30	236.89	1,740.19	97	CRITICAL
5	ATHANI	1,919.46	1,677.63	167.95	1,845.57	96	CRITICAL
6	BHAVANI	2,751.33	1,619.50	524.10	2,143.60	78	SEMI CRITICAL
7	BHAVANISAGAR	1,369.33	1,914.85	333.90	2,248.75	164	OVER EXPLOITED
ERODE DISTRICT							
Sl.No	Assessment Unit (Firka)	Net Annual Ground Water Availability	Existing Gross Ground Water Draft for Irrigation	Existing Gross Ground Water Draft for domestic and industrial water supply	Existing Gross Ground Water Draft for All uses (4+5)	Stage of Ground Water Development $\{(6/3)*100\}$ %	Category of the Firka
8	BURGUR	352.30	55.30	24.45	79.75	23	SAFE
9	CHENNIMALAI	1,922.76	2,713.10	43.98	2,757.08	143	OVER EXPLOITED
10	ELATHUR	2,078.15	2,503.83	59.00	2,562.82	123	OVER EXPLOITED
11	ERODE EAST	1,380.09	601.60	921.98	1,523.58	110	OVER EXPLOITED
12	ERODE NORTH	854.92	491.08	709.05	1,200.12	140	OVER EXPLOITED
13	ERODE WEST	1,431.92	1,283.00	68.45	1,351.45	94	CRITICAL

14	GOBICHETTIPALAYAM	3,702.39	1,673.65	228.42	1,902.07	51	SAFE
15	KANJIKOIL	2,122.56	1,851.95	27.81	1,879.76	89	SEMI CRITICAL
16	KASIPALAYAM	1,220.53	963.93	14.43	978.35	80	SEMI CRITICAL
17	KAVANDAPADI	3,878.49	2,872.75	153.99	3,026.74	78	SEMI CRITICAL
18	KILAMPADI	1,372.41	1,198.00	16.04	1,214.04	88	SEMI CRITICAL
19	KODUMUDI	1,536.67	2,174.05	148.44	2,322.49	151	OVER EXPLOITED
20	KUGALUR	2,859.84	1,250.30	59.18	1,309.48	46	SAFE
21	KURICHI	1,808.36	1,429.20	166.42	1,595.62	88	SEMI CRITICAL
22	KUTHIYALATHUR	1,197.47	921.50	18.12	939.62	78	SEMI CRITICAL
23	MODAKURICHI	2,320.64	2,419.45	451.11	2,870.56	124	OVER EXPLOITED
24	NAMBIYUR	975.26	2,389.60	120.94	2,510.54	257	OVER EXPLOITED
25	PERUNDURAI	1,064.02	1,694.88	515.46	2,210.34	208	OVER EXPLOITED
26	POONDURAI	2,672.71	1,734.90	53.07	1,787.97	67	SAFE
27	PUNJAIPULIAMPATTI	824.37	1,694.65	57.52	1,752.17	213	OVER EXPLOITED
28	SATHYAMANGALAM	2,298.15	1,780.50	239.96	2,020.46	88	SEMI CRITICAL
29	SIRUVALUR	1,861.53	1,571.70	57.73	1,629.43	88	SEMI CRITICAL
30	SIVAGIRI	2,560.79	1,647.95	59.55	1,707.50	67	SAFE
31	THALAVADI	2,638.77	1,966.85	81.89	2,048.74	78	SEMI CRITICAL
32	THINGALUR	1,736.23	1,491.05	41.05	1,532.10	88	SEMI CRITICAL
33	VANIPUTHUR	4,041.29	2,324.15	108.57	2,432.72	60	SAFE
34	VELLODE	1,401.36	1,639.60	48.62	1,688.22	120	OVER EXPLOITED
TOTAL		67,024.26	57,638.30	6,029.53	63,667.83	95	

4. Groundwater quality issues:

The rainfall is the main source for the availability of water both in surface and sub surface. The quantum of rainfall varies every year depending upon the monsoon. However, the extraction of surface and sub surface water is increasing year by year. It leads to environmental impact on the water sources like depletion of water level, deterioration of water quality. It makes the demand for the quantification of available water and also its quality for various purposes like agriculture, industries, drinking and domestic purposes.

For the present assessment, the value of Total Dissolved Solids (TDS) have been considered for demarcation of good / bad quality areas. For this purpose,

the TDS value of less than or equal to 2000 mg/l have been considered as good quality and the value more than 2000 mg/l have been considered as bad quality areas.

The presence of fluoride in natural Ground Water is having its merits and demerits depending upon the concentration. Presence of fluoride <1.0 mg/l in drinking water reduces dental diseases whereas higher level > 1.50 mg/l will affect the health and causes dental fluoridise. Nitrate is noted significantly in Ground Water due to use of chemical fertilizer for agriculture and other local pollution rocks and soils are also contributing nitrate to Ground Water. Arsenic is another poisonous heavy metal in Ground Water. The allowable limits for drinking purposes are 0.05 mg/l.

In Erode District, the quality of Ground Water generally ranges from moderate to good quality both in the shallow dug well and bore wells except in & around the Kazhuveli tank, where the water quality is poor due to seawater intrusion in the lagoons during high tide seasons, the production of salt and Aquaculture farming.

5. Groundwater issues and challenges:

The groundwater quantity and quality are to be highlighted and may be analyzed in terms of :

(i)Problems posed by nature:

In terms of Quantitative aspects, nowadays, rainfall may more within the short period of duration. Due to this aspect, recharge is less and runoff will be more. The availability of groundwater is less due to over extraction than recharge. The Percentage of OE/Critical Firkas increased due to this reason. Increasing the artificial recharge structures in the proper areas may avoid the depletion of groundwater especially in OE/Critical Firkas.

(ii) Problems caused by anthropogenic activities:

The problems caused due to intensive groundwater extraction, intensive surface water irrigation, intensive mining activities, growing urban complexes and industrial establishments will lead to drastic depletion in groundwater resources only. Proper alternative recharge structures must be established.

(iii) Problems caused by socio-economic condition:

The land holdings of farmers may be different from another. One farmer having more than 5 Acres has less expense than a farmer having one acre. The free electric supply to all farmers have chance to extract more groundwater. To avoid this, proper guidance will be given to the farmers for the usage of groundwater.

(iv) Administrative issues:

To control, regulate and manage the Ground Water Resources in the State, there is no groundwater act, now in force. But, the **Chennai Metropolitan Area Ground Water (Regulation) Act, 1987** is in force and it extends to Chennai City and notified 302 revenue villages in Kanchipuram and Thiruvallur Districts, only.

The rest of Tamilnadu, **G.O.(Ms).No.142, Public Works (R2) Department, dated: 23.07.2014** and **G.O.(Ms).No.113, Public Works (R2) Dept , Dt:09.06.2016** are regulate and manage the groundwater resources. The Government of Tamil Nadu had enacted the **Tamil Nadu Ground Water (Development and Management) Act, 2003**. However, this **Act was repealed on 14.09.2013**, in order to enact a comprehensive law to develop and manage the groundwater in the changed scenario in the State.

The pricing policy for groundwater users is also an important strategy in controlling the illegal extraction of groundwater by taking from lorries,etc. The unused dug wells and bore wells can be used as artificial recharge structures will be good concept in recharging the ground water.

6. Groundwater Management and Regulations:

(i) Statute/Law/Policy/Regulations if any:

The Central Ground Water Authority has been constituted to regulate, control, development and management of ground water resources for whole country based on overall situation prevailing in India. But, the ground water conditions are varying from State to State. **Ground Water is a State subject and the State Government has every right to protect and regulate their own precious ground water resources according to the prevailing conditions in the State.**

The Tamil Nadu Government had enacted “**The Tamil Nadu Ground Water (Development and Management) Act, 2003**” which was

subsequently **repealed in 2013**, so as to bring out an effective management Act considering the present scenario. **As an interim measure, for regulating the exploitation of ground water, the Government have issued G.O. (Ms) No.142,PWD dated 23.07.2014 for regulations for management of ground water for safe guarding the scarce groundwater resources in Tamil Nadu State.** In the absence of an Act, the Government executes this Government order to control, regulate and manage the Ground Water Resources while taking into consideration of the future of the State and its people.

The State Ground and Surface Water Resources Data Centre has estimated the Ground Water resources of Tamil Nadu State periodically in co-ordination with the Central Ground Water Board, Government of India, SECR, Chennai, based on the Methodology evolved by Ground Water Resources Estimation Committee, 1997 (GEC 97).

Accordingly, **the Ground Water Potential Assessment done as on January 1992 and as on January 1997 on the basis of Panchayat Union Blocks as assessment units** in Tamil Nadu and **categorized as Dark, Grey and White areas.** The Blocks with more than 85% to 100% ground water development were categorized as “Dark Blocks” and the blocks with ground water development between 65% to 85% were categorized as “Grey Blocks” and less than 65% ground water development were categorized as “White Blocks” and the Government approved the categorisation and released as Government order and G.O.No:326, PW (R2) Dept, dated: 23.11.1993. It was in effect up to the next assessment done as on March 2003.

Subsequently, **the Ground Water Potential Assessment done as on March 2003, categorized the blocks as Over Exploited, Critical, Semi Critical, Safe, Saline instead of Dark, Grey and White blocks.** The Blocks with more than 100% were categorized as “Over Exploited Blocks”, the blocks in between 90% to 100% as “Critical Blocks”, the blocks in between 65% to 90% as “Semi Critical Blocks” and less than 65% as “Safe Blocks” and the bad quality blocks were categorized as “Saline Blocks” and the same was approved by the Government and released as G.O.No:51, PW (R2) Dept, dated: 11.02.2004. It was in effect up to the next assessment done as on March 2009.

The Next **Ground Water Potential Assessment** done as on **March 2009**, and the same was approved by the Government and **released as G.O.No:52,PW(R2) Dept, dated: 02.03.2012.**

As per G.O.No.52,PW(R2) Dept, dated: 02.03.2012 and G.O. (Ms) No.142,PW(R2)Dept dated 23.07.2014, the State Government have authorized and empowered the Chief Engineer, State Ground and Surface Water Resources Data Centre, Chennai for issuing permission or license or No Objection Certificate/renewal for drawal and transportation of Ground Water based on the hydro geological conditions to the New Industries, Packaged Drinking Water Companies, Infrastructures and Mining projects, etc except the areas to which the Chennai Metropolitan Area Ground Water (Regulation) Act,1987 extends.

Subsequently, the next **Ground Water Resources Assessment of the State was completed as on March 2011** and taking **Firka as an assessment unit** in the State of Tamil Nadu. Based on the above assessment, **the Government had approved and issued G.O.(Ms).No.113, Public Works (R2) Dept , Dt:09.06.2016** for categorisation of the Firkas in the State as Over Exploited, Critical, Semi-Critical and Safe Firkas. All the Over Exploited and Critical Firkas are notified as **“A” Category** (where the stage of ground water extraction is 90% and Above) and all the Semi Critical and Safe Firkas are notified as **“B” Category** (where the stage of ground water extraction is below 89%). In this Government Order, the Government had directed that **no Schemes should be formulated in the “A” Category Firkas and in “B” Category Firkas, all the Schemes should be formulated through State Ground and Surface Water Resources Data Centre by issuing No Objection Certificate for Ground Water Clearance.**

The term “Schemes” excludes Energisation of Agricultural pump sets by the Tamil Nadu Electricity Board. The present order may also exclude the Ground Water drawal for a). Domestic purpose by individual household, b). Domestic Infrastructure project (Housing), c).Government’s Drinking Water Supply Schemes and d). non water based industries, (i.e.- the industries which do not require and use water, either as raw material or for other processing). However, the domestic use of water by this non water based industries will be permitted by the Chief Engineer / State Ground and Surface Water Resources Data Centre based on hydro geological

conditions. (i.e. NOC from Chief Engineer, State Ground and Surface Water Resources Data Centre, Water Resources Department, Chennai). The list of non water based industries will be issued by the Industries Department of Government of Tamil Nadu separately.

Appropriate rain water harvesting and Artificial recharge schemes should be carried out in the categories viz , Over exploited , Critical , Semi Critical and Safe blocks of Tamil Nadu. While carrying out the above schemes, priority should be given to marginal quality and bad quality areas so as to avoid further deterioration.

All the schemes and proposals based on Ground Water will have to adhere to the Government orders and conditions. The Chief Engineer, State Ground and Surface Water Resources Data Centre had received the Government approval on Groundwater Assessment as on March 2011.

Regarding granting permission/ License for transportation of ground water for water suppliers/ private water tankers for selling the water on commercial basis, the State Ground and Surface Water Resources Data Centre, Public Works Department is not issuing any No Objection Certificate.

The Chief Engineer, SG&SWRDC have empowered to issue the NOC for drawal of Ground Water is up to 1 Million Gallons per day. Beyond this, the firms should get an approval in Water Utilisation Committee for drawal of both Surface and Ground Water resources in Tamil Nadu.

(ii) Suggestions for improvement of groundwater governance.

Groundwater is recognized as a common pool resource. The use of groundwater by anybody should in no way cause adverse impacts on realization of other person's fundamental right to safe water for life. Access to groundwater without any discrimination, equitable distribution, and sustainable use considering the needs of future generations are considered. Right to water for life is the first priority and then to agriculture, and eco system needs. The precautionary principle and the polluter pay principle only to conserve and recharge groundwater.

The responsibility of the State for ensuring every person's right to safe water even when water service is delegated to a private agency. Groundwater is not amenable to ownership by the State, communities or persons and the State is the public trustee of groundwater. It also deals elaborately on groundwater protection and groundwater security plans.

The Groundwater Act should incorporate legal pronouncement on groundwater such as the public, trust doctrine and recognition of the right to groundwater. It addresses the deficiencies in the present legal frame work in dealing with over exploitation and includes the improvements to the control mechanism to ensure the qualitative and quantitative sustainability of groundwater resources. It proposes to strengthen the regulating powers of Panchayat and Municipal bodies related to Ground water in line with articles 243G and 243W of the constitution.

The Pricing of Ground Water for irrigation, Industrial and domestic purposes and collecting fees by water users association should be left to the State decision.

(iii) Institutions governing/managing/monitoring the resources and Institutional structure, gaps if any :

While framing the Groundwater Act, the recommendation for the constitution of (1) Gram Panchayat Groundwater Sub-Committee, (2) Block Panchayat Groundwater Management, (3) Ward Groundwater Committee, (4) Municipal Water Management Committee, (5) District Ground Water Council and (6) State Ground Water Advisory Council to control and manage Ground water should be considered.

- The constitution of aforesaid committees is completely based on administrative boundaries such as village, block, ward, municipality, district etc. But, with respect to water resources control and management issues and conflicts, the boundary should be based on river basins to have efficient monitoring and management of water resources. The Government of India, in all issues related to water resources considered only the basin boundary concept. Hence, the institutional frame work has to be revised so as to have the jurisdiction of the committees with respect to basin / watershed concept. Further, Government of

India, MoWR, RD &GR advocates time and again integrated water resources management. The above institutional frame work separately for groundwater is not in line with that.

- Further, it has also provided for many committees, viz., Gram Panchayat Groundwater Sub-Committee, Village Water and Sanitation Committee, Ward Committee, Municipal Committee, Block level Committee, District level Committee and State level Committee. For managing surface water resource water users association already exists. Too many committees at village / ward level would jeopardize the very purpose of managing the Groundwater resources efficiently and may invite lot of conflicts.

(iv) Areas of people/private participation if any:

The participation of people or private parties in the groundwater management is not suggestible, acceptable one and more chances of making litigations in the society and has unnecessary law and order problems may arise.

7. Tools and Methods

(i) Water Level and quality measurements through wells, piezometers, DWLR with telemetry, ground water elevation.

In general, water levels in the observation wells and piezometers can be taken manually by measuring tape. This is the simple, cost effective, good accuracy and less maintenance method. Water Levels are observed above the Measuring point.

Monitoring water level in DWLR with telemetry is costly, high maintenance, good accuracy, get the data immediately on desktop, easy to analysis purpose.

The water quality generally is analysed in the Chemical Lab only by collecting water samples in Pre Monsoon and post Monsoon period in the field. Sometimes, instant kits are used for analyzing the TDS and Ph level in the water.

(ii) Metering water supply to confirm contribution from groundwater.

Metering the water supply is essential one to monitor the overall usage of groundwater by different sectors. Flow meter must be fixed in every extraction structure and it has to be monitored periodically by Government officials.

8. Performance Indicators:

(i) Bench Marks/ Norms/ Standards and deviation from the norms/bench marks/ standards currently.

The Ground Water resources of State periodically estimated in co-ordination with the Central Ground Water Board, Government of India, SECR, Chennai, based on the Norms evolved by Ground Water Resources Estimation Committee, 1997 (GEC 97).

The ground water potential assessment can be assessed based on the bench marks such as Average Rainfall, Total recharged Area, Monthly Water Level Data, Total no of wells in the area, Irrigation methods adopted, Cropping pattern details, Geological conditions prevailing in that area, Specific yield, Seepage factor, Constructed Artificial recharge structures, etc and various calculations methods, etc, have to be considered.

Status of various Performance Indicators

(ii) Percentage of over exploited ,critical, Semi critical , Safe and Saline/Poor quality Firkas/area units

- Trend of over exploited and critical Firkas to total Firkas as per pervious assessment. (2009 Assessment Vs 2011 Assessment)

The Ground Water Potential Assessment as on March 2009, Out of 14 blocks in Erode District, 1 blocks are categorized as Over Exploited and Critical blocks and remaining 13 blocks are categorized as Semi Critical and Safe blocks.

The next Ground Water Resources Assessment of the State was done as on March 2011 and taking Firka as an assessment unit. In Erode District, totally 34 Firkas, 12 Firkas are categorized as Over Exploited and remaining 22 Firkas are categorized as Semi Critical and Safe blocks.

Instead of taking Block as an assessment, Firka can be taken as assessment unit is to concentrate the assessment in micro level. For Eg, a block contains more than three to four Firkas. In this block, two Firkas may have good groundwater potential than other two Firkas but it may to categorize as Over Exploited. To avoid this, assessment done on the basis of Firkas for the benefit of farmers to the implementation of schemes related to Irrigation.

The percentage of over exploited and critical Firkas has been increased by changing the concept from Block to Firka assessment. The total percentage of over exploited and critical Blocks for 2009 Assessment is 7.14%, but, the total percentage of over exploited and critical Firkas as on March 2011 Assessment is 35.29%, in the Erode District.

- Trend of over exploited and critical Firkas to total Firkas as per latest assessment

The percentage of over exploited and critical Firkas has been decreased in 2013 latest assessment when compared to 2011 assessment. In 2011 assessment, out of 34 Firkas, the total percentage of over exploited and critical Firkas is 35.29%, but, In 2013 assessment, out of 34 Firkas, it has been come down marginally to 50%, in the Erode District.

- Existing state of groundwater resources as compared to previous assessment (2013 Vs 2011 assessment).

Based on the Estimation of Ground Water Resources of Tamil Nadu State as on March 2013, Out of 34 Firkas in the District, 12 Firkas are categorized as “Over Exploited Firkas”, 5 Firkas are categorized as “Critical Firkas”, 11 Firkas are categorized as “Semi Critical Firkas”, 6 Firkas are categorized as “Safe Firkas”.

Based on the Estimation of Ground Water Resources of Tamil Nadu State as on March 2011, Out of 34 Firkas in the District, 11 Firkas are categorized as “Over Exploited Firkas”, 1 Firkas are categorized as “Critical Firkas”, 18 Firkas are categorized as “Semi Critical Firkas”, 4 Firkas are categorized as “Safe Firkas”.

When compared to last assessment as on March 2011, the “Over Exploited Firkas” increased from 11 to 12 Firkas, the “Critical Firkas” increased from 1 to 5 Firkas, the “Semi Critical Firkas” decreased from 18 to 11 Firkas, the “Safe Firkas” increased from 4 to 6 Firkas and the “Saline Firkas” remains Nil Firkas. The alteration of Firkas are due to the construction of Artificial Recharge structures such as Check Dams, Recharge Wells, Recharge shafts, percolation ponds; etc was constructed in the “Over Exploited Firkas” by various departments.

S.No	Categorisation	No of Firkas	
		2011	2013
1	Over Exploited	11	12
2	Critical	1	5
3	Semi Critical	18	11
4	Safe	4	6
5	Saline	Nil	Nil
TOTAL		34	34

(iii) Water Level(Well hydrographs and water level trends – pre and post monsoon such as declining trend/rising trend,etc).

(iv) Comparison of area irrigated from groundwater resources (Current assessment 2013 to previous assessment 2011).

S.No	Description	2011 Assessment	2013 Assessment
1	Area Irrigated from ground water resources(In hm)	6538.07	6505.06

(v) No. of groundwater abstraction structures (existing no. over the year and trends).

S.No	Description	2011 Assessment	2013 Assessment
1	No of groundwater abstraction structures for Irrigation	1,71,071 Wells	1,70,983 Wells

(vi) Trend in water quality (no of habitations affected with groundwater contamination like As, F, Salinity etc. Change in contamination level over the years.

(vii) Source augmentation (Groundwater)

- Area covered with infrastructure for recharging groundwater:

The proper artificial recharge structures has to be constructed based on local geological conditions in the areas of existing infrastructure for recharging groundwater according to their extraction needs.

- GW recharge plan to combat adversaries:

Groundwater recharge plans has to be strictly followed by with of implementing the groundwater laws to combat adversaries.

9. Reforms undertaken/being undertaken/proposed if any.

10. Road Map of activities/tasks proposed for better governance with timelines and agencies responsible for each task/activity.